

# PRODUCT DATASHEET



## Prolab<sup>®</sup> Faceplate / General Labels - Self-adhesive



This is a multipage document, all pages must be read in conjunction with each other



The Silver Fox Prolab<sup>®</sup> faceplate / general self-adhesive labels incorporate a special laser print-receptive surface ensuring the best quality of print every time. The adhesive is acrylic and designed to give long-term bonding. A smooth, clean, dry metal or plastic surface is required.

These labels can be used for a wide range of applications including faceplates, outlets and control panels. They are also suitable for general labelling.

Available in packs of 10 or 100 sheets.

### TECHNICAL DATA

<b>Printing Method</b>	Standard Laser Printer
<b>Material</b>	Self-adhesive Polyester
<b>Thickness</b>	50 microns
<b>Sheet Size</b>	A4
<b>Standard Colours</b>	See order information
<b>RoHS (EU 2002/95/EC)</b>	RoHS Compliant

### PRODUCT TESTING

Test	Method
Moisture Resistance	MIL-STD-202G Method 106G
Low Temperature 72 hours @ -40°C	MIL-STD-810F Method 502.4
High Temperature 2000 hours @ 70°C to 100°C*	MIL-STD-202G Method 108A
Hydrogen Sulphide	H <sub>2</sub> S Sour Gas Exposure (2% H <sub>2</sub> S)
UV Weathering 3000 hours**	ISO 4982 Part 3 Method A Cycle 1
Salt Mist Spray	IEC60068-2-52 Test Kb Salt Mist (Cyclic)

\* Samples were subjected to 500 hours @ 70°C, followed by 500 hours @ 85°C followed by 1000 hours @ 100°C

Note: This label is designed for internal use. For external use the user must determine the suitability of this label for their particular application. White material tested for all tests.

\*\* White label tested for our evaluation purposes. All label colours are intended for internal use only. It is always the responsibility of the user to determine the suitability of all label types for their particular application.

### FEATURES & BENEFITS

- Print using a standard office laser printer
- Pre-cut for rapid removal from sheet
- Fits a wide range of applications
- Available in a range of different sizes to suit your needs
- To help you identify the label size you require, our product codes are named with the label dimensions. i.e., PC/TAG/2008L = 20mm x 8mm

**etech**  
components

All Enquiries:

tel: +44 (0)1744 762 929

email: [sales@etechcomponents.com](mailto:sales@etechcomponents.com)

web: [www.etechcomponents.com](http://www.etechcomponents.com)

# PRODUCT DATASHEET

## Prolab<sup>®</sup> Faceplate / General Labels - Self-adhesive



This is a multipage document, all pages must be read in conjunction with each other



### STORAGE INSTRUCTIONS

<b>Storage Instructions</b>	Store between 50° F (10° C) and 77° F (25° C)
<b>Shelf Life</b>	2 Years
<b>Conditions</b>	Keep in dark conditions
<b>Humidity Resistance</b>	35% to 65% RH

### ORDER INFORMATION


Product Code	Label Dims (mm)	Labels per Sheet	Sheets per Pack	Labels per Pack	Colour Options
P/TAG/1212L*	12 x 12	320	10 / 100	3200 / 32000	
P/TAG/1438L*	14 x 38	84	10 / 100	840 / 8400	
P/TAG/1506L*	15 x 6	504	10 / 100	5040 / 50400	
P/TAG/1512L*	15 x 12	240	10 / 100	2400 / 24000	
P/TAG/1608L*	16 x 8	360	10 / 100	3600 / 36000	
P/TAG/1709L*	17 x 9	308	10 / 100	3080 / 30800	
P/TAG/2207L*	22 x 7	288	10 / 100	2880 / 28800	
P/TAG/2412L*	24 x 12	160	10 / 100	1600 / 16000	
P/TAG/2610L*	26 x 10	161	10 / 100	1610 / 16100	
P/TAG/3007L*	30 x 7	210	10 / 100	2100 / 21000	
P/TAG/3030L*	30 x 30	40	10 / 100	400 / 4000	
P/TAG/3318L*	33 x 18	65	10 / 100	650 / 6500	
P/TAG/3812L*	38 x 12	100	10 / 100	1000 / 10000	
P/TAG/4809L*	48 x 9	112	10 / 100	1120 / 11200	
P/TAG/5522L*	55 x 22	33	10 / 100	330 / 3300	
P/TAG/6036L*	60 x 36	21	10 / 100	210 / 2100	
P/TAG/29730L*	297 x 30	7	10 / 100	70 / 700	
P/TAG/A5L*	148 x 210	2	10 / 100	20 / 200	
P/TAG/A4L*	297 x 210	1	10 / 100	10 / 100	

\*Specify colour and pack size when ordering. Please Note: Colours shown are for indicative purposes only – shades may vary.


Represents a clear label.

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice.

### SILVER FOX CATALOGUE



### TIP - TIME INTO PROFIT BROCHURE



**etech**  
components

All Enquiries:

tel: +44 (0)1744 762 929

email: sales@etechcomponents.com

web: www.etechcomponents.com