



Plastic Two Bolt Cleat 374 series

- Suitable for use with cable diameters 50 to 94mm.
- Manufactured from black high-density nylon 66.
- Unaffected by corrosive environments such as oils and many chemicals.
- Sunlight (UV) and weather resistant.
- Two-piece, two fixing design.
- Can be double stacked on common fixings.
- Operating temperature -25°C to +85°C.
- Tested in accordance with BS EN 50368.

SINGLE WAY CLEATS

Technical Data

| Cable and Cleat Selection | | | Cleat Details | | | | Weight (g) |
|---------------------------|----------------|-----|---------------|-----------------|----|-----|------------|
| Design Number | Cable diameter | | B | Dimensions (mm) | | | |
| | A (mm) | | | C | D | E | |
| | Min | Max | Max | | | | |
| 374AA01 | 50 | 58 | 89 | 102 | 45 | 80 | 97 |
| 374AA02 | 56 | 64 | 93 | 102 | 45 | 80 | 98 |
| 374AA03 | 62 | 70 | 98 | 114 | 45 | 92 | 106 |
| 374AA04 | 68 | 76 | 104 | 114 | 50 | 92 | 132 |
| 374AA05 | 74 | 82 | 110 | 126 | 50 | 104 | 154 |
| 374AA06 | 80 | 88 | 118 | 126 | 50 | 104 | 160 |
| 374AA07 | 86 | 94 | 121 | 136 | 60 | 114 | 204 |

Method of Fixing

In all applications the cleat should be mounted on suitable M10 fixings. There is no need for any channel adaptor when mounting directly on to 'C' section channel.

Performance Data

| | |
|--------------------------|-------------------------------|
| Test Standard | EN 50368:2003 |
| Type | 6.1.2 Non-Metallic |
| Impact Resistance | 6.2.4 Heavy -> 6.2.5 V. Heavy |
| Lateral Load | 10.9 -> 14.8 kN |
| Axial Load | 198 -> 494 N |
| Needle Flame | >120 secs |

* Technical Information subject to change without notice

