



# Afumex Two Bolt Cleat (LSOH) 374 series

- Suitable for use with cable diameters 50 to 94mm.
- Manufactured from LSOH Polymer.
- Designed for use with Afumex LSOH and Saffire OHLS cables.
- Low Smoke and Zero Halogen.
- Sunlight (UV) and weather resistant.
- Two-piece, two fixing design.
- Can be double stacked on common fixings.
- Operating temperature -40°C to +60°C.
- Tested in accordance with BS EN 50368.
- LUL approved product register ID 1958.

SINGLE WAY CLEATS

## Technical Data

**Afumex SAFFIRE<sup>OHLS</sup>**

Cable and Cleat Selection			Cleat Details					
Design Number	Cable Diameter		Dimensions (mm)					Weight (g)
	A (mm)		B	C	D	E		
	Min	Max	Max					
374LSF01	50	58	89	102	45	80	174	
374LSF02	56	64	93	102	45	80	158	
374LSF03	62	70	98	114	45	92	174	
374LSF04	68	76	104	114	50	92	210	
374LSF05	74	82	110	126	50	104	254	
374LSF06	80	88	118	126	50	104	264	
374LSF07	86	94	121	136	60	114	326	

### Method of Fixing

In all applications the cleat should be mounted on suitable M10 fixings. There is no need for any channel adaptor when mounting directly on to 'C' section channel.

## Performance Data

<b>Test Standard</b>	EN 50368:2003
<b>Type</b>	6.1.2 Non-Metallic
<b>Impact Resistance</b>	6.2.5 V. Heavy
<b>Lateral Load</b>	1.22 -> 3.485 kN
<b>Axial Load</b>	82 -> 110 N
<b>Needle Flame</b>	>120 secs

\* Technical Information subject to change without notice

