



AP Clips

- Suitable for Prysmian FP200 Gold®, FP Plus™, FP Plus Flex™ and Afumex LSX™.
- Suitable for Draka FT30, FT120 and FT Data.
- Securely holds one cable - ideal for a single cable run.
- Made from BS EN 1652 copper strip.
- Fire tested with FP cables.
- Finished with a red or white LSOH polyester coating.
- Ideal for visible installations.
- Meets the cable support requirements of BS 5839-1:2002+A2:2008.

FIRE RESISTANT CLEATS

Technical Data



Style	Clip Selection		Cable Diameter		Clip Details				
	Design Number		(mm)		Clip Dimensions (mm)				
	Red	White	Min	Max	B	C	D	Ø E	F
AP7	386PR07	386PW07	7.8	8.2	24	1.5	10	4.25	4.5
AP8	386PR08	386PW08	8.3	8.8	26	1.5	10	4.25	4.5
AP9	386PR09	386PW09	9	9.9	27	1.5	10	4.25	4.5
AP10	386PR10	386PW10	10	10.9	30	1.5	10	4.25	4.5
AP11	386PR11	386PW11	11	11.9	32	1.5	10	4.25	4.5
AP12	386PR12	386PW12	12	12.9	33	1.5	10	4.25	4.5
AP13	386PR13	386PW13	13	13.9	37	1.5	10	4.25	4.5
AP14	386PR14	386PW14	14	14.9	38	1.5	10	4.25	4.5
AP15	386PR15	386PW15	15	15.9	40	1.5	10	4.25	4.5
AP16	386PR16	386PW16	16	16.9	40	1.5	10	4.25	4.5
AP18	386PR18	386PW18	18	18.9	52	1.5	15	4.25	4.5
AP20	386PR20	386PW20	20	20.9	56	1.5	15	4.25	4.5
AP22	386PR22	386PW22	22	22.9	60	1.5	15	4.25	4.5
AP25	386PR25	386PW25	25	25.9	65	1.5	15	4.25	4.5

