



Two Bolt Cleat (Cast Iron) 370 series

- Suitable for use with cable diameters 51 - 89mm.
- Hot dip galvanised finish on cast iron.
- Two-piece, two fixing design.
- Can be double stacked on common fixings.
- Operating temperature -60°C to +105°C.
- Can withstand a 2 hour excursion to 1000°C.
- Can be used for all types of cable routes.
- Suitable for all environments.
- LUL Approved product register ID 1964.
- Allows fire performance cables to meet the requirements of BS 6387:1994, BS 5839-1:2002, BS7346-6:2005 & BS8491:2008.



Technical Data

Cable and Cleat Selection			Cleat Details					Weight (g)	Stud Size
Design Number	Cable diameter		Dimensions (mm)						
	A (mm)		B	C	D	E			
	Min	Max	Max						
370CG10	51	59	75	98	49	76	902	M10	
370CG11	54	62	78	102	49	80	892	M10	
370CG12	57	65	81	105	49	82	854	M10	
370CG13	62	70	89	137	64	114	1155	M10	
370CG14	68	76	95	140	64	114	1245	M12	
370CG15	74	82	102	140	64	114	1300	M12	
370CG16	80	89	108	140	64	114	1582	M12	

Method of Fixing

In all applications the cleats should be mounted on suitable fixings, see table for appropriate size. When mounting directly on channel, adaptor plate 380AG02 should be used. (Please see page 39).

Performance Data

Test Standard	EN 50368:2003
Type	6.1.1 Metallic
Impact Resistance	6.2.5 V. Heavy
Lateral Load	18.1 kN
Axial Load	11.4 kN
Needle Flame	>120 secs

* Technical Information subject to change without notice

