

Tube terminals 90° degrees 10 - 150 mm², KRF

- Data: electrolytic copper, tin plated.
- Cable inspection hole, for stranded (class 2) and flexible (class 5) Cu-conductors.
- UL-approved (35-150 mm²). DNV-approved (16-150 mm²).

Marking example KRF: 70 10F (Elpress logotype included)

70 = mm² 10 = palm hole for M10 F = type KRF, for stranded and flexible conductors



AWG	Cat. no. mm ² , Bolt	mm W	d	N	N ₁	A	Pcs/ pack	Die no.	Rec. tool
8	KR10-6-90GR	13,0	5,0	6,5	11,5	15	100	8	V600, V1300
8	KR10-8-90GR	13,5	5,0	8,5	12,0	15	100	8	V600, V1300
6	KRF16-6-90GR	13,0	6,0	6,5	11,5	16,5	100	9	V600, V1300
6	KRF16-8-90GR	13,5	6,0	8,5	12,0	16,5	100	9	V600, V1300
4	KRF25-6-90GR	17,0	8,0	6,5	11,5	18,5	100	11	V600, V1300
4	KRF25-8-90GR	17,0	8,0	8,5	12,0	18,5	100	11	V600, V1300
4	KRF25-10-90GR	17,0	8,0	11,5	13,5	18,5	100	11	V600, V1300
2	KRF35-6-90GR	18,0	9,0	6,5	11,5	22,5	100	13	V600, V1300
2	KRF35-8-90GR	18,0	9,0	8,5	12,0	22,5	100	13	V600, V1300
2	KRF35-10-90GR	18,0	9,0	11,5	13,5	22,5	100	13	V600, V1300
1/0	KRF50-8-90GR	21	11,0	8,5	17,5	30,5	100	14,5	V600, V1300
1/0	KRF50-10-90GR	21	11,0	11,5	18,5	30,5	100	14,5	V600, V1300
1/0	KRF50-12-90GR	21	11,0	12,5	19,5	30,5	100	14,5	V600, V1300
2/0	KRF70-8-90GR	25	13,0	8,5	17,5	31,5	50	17	V600, V1300
2/0	KRF70-10-90GR	25	13,0	11,5	18,5	31,5	50	17	V600, V1300
2/0	KRF70-12-90GR	25	13,0	12,5	19,5	31,5	50	17	V600, V1300
4/0	KRF95-10-90GR	29	15,0	11,5	18,5	32,5	50	20	V600, V1300
4/0	KRF95-12-90GR	29	15,0	12,5	19,5	32,5	50	20	V600, V1300
4/0	KRF95-16-90GR	29	15,0	15,5	20,5	32,5	50	20	V600, V1300
250	KRF120-10-90GR	32	17,0	11,5	18,5	34,5	25	22	V1300, V250
250	KRF120-12-90GR	32	17,0	12,5	19,5	34,5	25	22	V1300, V250
250	KRF120-16-90GR	32	17,0	15,5	20,5	34,5	25	22	V1300, V250
300	KRF150-10-90GR	36	19,0	11,5	18,5	37,5	25	25	V1300, V250
300	KRF150-12-90GR	36	19,0	12,5	19,5	37,5	25	25	V1300, V250
300	KRF150-16-90GR	36	19,0	15,5	20,5	37,5	25	25	V1300, V250

For detailed information regarding recommended tool or system, see chapter 6.