

Certified Miniforce tools for pre-insulated terminals 0.5 - 6 mm² and end terminals 0.25 - 4 mm²



Technical data:

- unique mechanism that reduces maximum handle force with 30% compared to the earlier Exx version
- ratchet system to guarantee a fully closed crimp
- release mechanism if the crimping sequence must be interrupted
- symmetrical and distinctly laser marked die nests
- adjustable if changes occur, ie after many crimps
- tested with Elpress terminals
- ergonomically designed handles to fit all users
- optimises the quality of the crimp result
- reduces the risk for repetitive strain injuries (RSI)
- light and handy design without reduction in durability
- type C has extra long handles for two hand grip
- at least 80 000 crimps
- delivered with certificate for quality assurance

Crimp range 0.25 - 4 mm²

GSEA0340C

Miniforce **combination crimp tool** for crimping of both;

- pre-insulated terminals 0.5 - 2.5 mm² and
- pre-insulated and un-insulated end terminals 0.25 - 4 mm²

Area	Cat. no.	Crimp types	Weight	Length x Width
0.25-4 mm ²	GSEA0340C	oval, symmetrical, trapezoid	0.682 kg	255 x 72 mm

GSEA0340C



Crimp types



Crimp range 0.5 - 6 mm²

GSW0560C

Miniforce crimp tool for through connectors with **heat shrink insulation** type SKW. Dies nest specially designed for crimping of the through connectors with heat shrink insulation – know as the SKW type. Use of other tools will destroy/harm the insulation leaving un-insulated openings direct to the terminal.

Area	Cat. no.	Crimp types	Weight	Length x Width
0.5-6 mm ²	GSW0560C	oval, symmetrical	0.678 kg	255 x 72 mm

GSW0560C



Crimp type

