

## You complete your kit with these dies

Additional dies to Elpress Mobile. All dies have the same easy and fast fastening in the frame.  
The dies are kept together as pairs and delivered in a plastic cassette which can be put together with other cassettes.



**OAA0160**  
For crimping of pre-insulated terminals 0.1 - 0.5 & 4 - 6 mm<sup>2</sup>.



**OAA0525**  
For crimping of pre-insulated terminals 0.5 - 2.5mm<sup>2</sup>.



**OSW0360**  
For crimping of through connectors with heat shrink insulation 0.3-0.75 and 4-6 mm<sup>2</sup>



**OSW0525**  
For crimping of through connectors with heat shrink insulation 0.5-1.5 and 1.5-2.5 mm<sup>2</sup>



**OPB0140**  
For crimping of global power connectors, GPC.



**OPB6099**  
For crimping of global power connectors, GPC.



**OWB4099**  
For W-crimping of un-insulated terminals 4 - 10 mm<sup>2</sup>.



**OKB0725**  
For indent crimping of un-insulated terminals 0.75 - 2.5 mm<sup>2</sup>.



**OKB0560**  
For indent crimping of un-insulated terminals 0.5 - 6 mm<sup>2</sup>.



**OEB0210**  
For crimping of end terminals 0.25 - 10 mm<sup>2</sup>.



**OEB1625**  
For crimping of end terminals 16 - 25 mm<sup>2</sup>.



**OEB3550**  
For crimping of end terminals 35 - 50 mm<sup>2</sup>.



**ORB0110**  
For roll crimping of terminals 0.1 - 1.0 mm<sup>2</sup>.



**ORB0560**  
For roll crimping of terminals 0.5 - 6 mm<sup>2</sup>.



**OMP45**  
For crimping of modular-plug RJ45.



**OMP11**  
For crimping of modular-plug RJ11.



**OFO5432**  
For crimping of fiber optics connections type ST, SC, SMA, SMB, SFR.



**OCC0908**  
For crimping of coaxial contacts type BNC, TNC, RG174, RG179.



**OCC1113**  
For crimping of coaxial contacts type BNC, TNC, RG58, RG59, RG62, RG71.



**OCC4755**  
For crimping of coaxial contacts type CATV, RG6, RG59.



**OMS4**  
For crimping of solar connectors Ø 4 mm, with open barrel conductor crimp 2.5 - 6.0 mm<sup>2</sup>.



**OMS3**  
For crimping of solar connectors Ø 3 mm, turned pin type 2.5- 6.0 mm<sup>2</sup>.



**OMSL**  
For crimping of solar connectors turned pin type Solar Lock 2.5- 6.0 mm<sup>2</sup>.

