

Pin terminals 0.1 - 6 mm²

■ Data: Cu 99.95%, tin plated, brazed necks.

■ PC sleeves have EasyEntry, PC and PA sleeves are halogen free.



mm ²	Cat. no.	mm W	d	L ₁	L	s	Pcs/ pack	Rec. tool	Insulation
0,1-0,5	A0514SR	1,4	2,0	8,0	18,0	6	100	DSA0115	PA*
0,25-0,75	A0819SR	1,8	3,2	12,0	22	7	100	DSA0115	PC
	A0819SRK	1,8	3,2	8,5	18,5	7	100	DSA0115	PC
0,5-1,5	A1519SR	1,7	4,0	12,0	22	7	100	GSA0760	PC
	A1519SRK	1,7	4,0	8,5	18,5	7	100	GSA0760	PC
1,5-2,5	A2519SR	1,9	4,5	11,5	21,5	8	100	GSA0760	PC
	A2519SRK	1,9	4,5	8,5	18,5	8	100	GSA0760	PC
4-6	A4630SR	2,7	6,4	14,0	27	9	100	GSA0760	PC

s = strip length * no EasyEntry

Blade terminals 0.25 - 6 mm²

■ Data: Cu 99.95%, tin plated, brazed necks.

■ PC sleeves have EasyEntry, PC and PA sleeves are halogen free.



mm ²	Cat. no.	mm W	d	t	L ₁	L	s	Pcs/ pack	Rec. tool	Insulation
0,25-0,75	A0825SFK	2,5	3,2	0,5	10,0	20	7	100	DSA0115	PC
0,5-1,5	A1518SFL	2,3	4,6	0,8	18,0	27	7	100	GSA0760	PVC
	A1529SF	2,9	4,0	0,7	12,0	22	7	100	GSA0760	PC
	A1529SFN	2,9	4	0,7	12	22	7	100	GSA0760	PC**
	A1530SFB	3,0	4,5	0,8	17,5	27	7	100	GSA0760	PVC
1,5-2,5	A2524SFL	2,4	4,5	0,8	18,0	28	8	100	GSA0760	PVC
	A2529SF	2,9	4,3	0,7	11,5	21,5	8	100	GSA0760	PC
	A2529SFN	2,9	4,3	0,7	12	22	8	100	GSA0760	PC**
	A2530SFB	3	4,6	0,7	17,5	27	8	100	GSA0760	PVC
4-6	A4640SF	4	6,7	1,0	13,0	27	9	100	GSA0760	PVC*
	A4645SFB	4,5	6,7	1,0	17,5	32	9	100	GSA0760	PVC*

t = palm thickness s = strip length * no EasyEntry ** with tab

Through connectors 0.25 - 6 mm²

■ Data: Cu 99.95%, tin plated.

■ Insulation sleeves are halogen free, no EasyEntry.



mm ²	Cat. no.	mm d	L	s	Pcs/ pack	Rec. tool	Insulation
0,25-0,75	A0824SK	2,9	24,5	7	100	DSA0115	PC
0,5-1,5	A1525SK	3,4	24	7	100	GSA0760	PC
1,5-2,5	A2527SK	4,3	26	8	100	GSA0760	PC
4-6	A4652SK	6,5	33	9	50	GSA0760	PC

s = strip length

For detailed information regarding recommended tool, see tool section at the end of this chapter.