

Bullets 0.25 - 6 mm²

■ Data: brass/Cu, tin plated.

■ PC sleeves have EasyEntry, PC and PA sleeves are halogen free.



mm ²	Cat. no.	mm d	L	Diameter	s	Pcs/ pack	Rec. tool	Insulation
0,25-0,75	A0802HA	3,6	26	2,0	7	100	DSA0115	PA*
0,5-1,5	A1504HA	4,0	22	4,0	7	100	GSA0760	PC
1,5-2,5	A2505HA	4,3	20	5,0	8	100	GSA0760	PVC*
4-6	A4605HA	6,6	26	5,0	9	100	GSA0760	PA*

s = strip length * non-brazed with reinforcement sleeve, no EasyEntry.

Sockets, fully insulated 0.25 - 6 mm²

■ Data: brass/tin bronze/Cu, tin plated.

■ PC sleeves have EasyEntry, PC and PA sleeves are halogen free.



mm ²	Cat. no.	mm d	L	For bullets diam.	s	Pcs/ pack	Rec. tool	Insulation
0,25-0,75	A0802HO	3,4	24	2,0	7	100	DSA0115	PA*
0,5-1,5	A1504HO	4,0	25	4,0	7	100	GSA0760	PC**
1,5-2,5	A2505HO	4,3	26	5,0	8	100	GSA0760	PVC*
4-6	A4605HO	5,7	27	5,0	9	100	GSA0760	PA*

s = strip length * non-brazed with reinforcement sleeve

** made from tin bronze (phosphorous bronze), EasyEntry

For detailed information regarding recommended tool, see tool section at the end of this chapter.