

## Receptacles 0.1 - 6 mm<sup>2</sup>

■ Data: brass or tin bronze, tin plated, brazed necks.

■ PC sleeves have EasyEntry, PC and PA sleeves are halogen free.



	mm <sup>2</sup>	Cat. no.	mm d	L	For tabs	s	Pcs/ pack	Rec. tool	Insulation
Yellow	0,1-0,5	A0503FLS5	2,3	16,0	2,8x0,5	7	100	DSA0115	PVC*
		A0503FLS8	2,3	16,0	2,8x0,8	7	100	DSA0115	PVC*
Red	0,5-1,5	A1503FLS5	3,3	18,5	2,8x0,5	7	100	GSA0760	PC
		A1503FLS8	3,3	18,5	2,8x0,8	7	100	GSA0760	PC
		A1505FLS5	3,7	19,0	4,8x0,5	7	100	GSA0760	PVC
		A1505FLS8	3,7	19,0	4,8x0,8	7	100	GSA0760	PVC
		A1507FLS	4,0	20	6,3x0,8	7	100	GSA0760	PC
		A1507FLST	4,0	20	6,3x0,8	7	100	GSA0760	PC**
Blue	1,5-2,5	A2505FLS5	4,4	19,0	4,8x0,5	8	100	GSA0760	PVC
		A2505FLS8	4,4	19,0	4,8x0,8	8	100	GSA0760	PVC
		A2507FLS	4,5	20	6,3x0,8	8	100	GSA0760	PC
		A2507FLST	4,5	20	6,3x0,8	8	100	GSA0760	PC**
		A2508FLS	4,3	24	8,4x0,8	8	100	GSA0760	PVC***
Yellow	4-6	A4607FLS	6,4	24	6,3x0,8	9	100	GSA0760	PC
		A4609FLS	6,2	31	9,5x1,2	9	100	GSA0760	PVC***

s = strip length \* no EasyEntry \*\* made from tin-bronze (phosphorus bronze)

\*\*\* not brazed, reinforcement sleeve, no EasyEntry.

## Multiple tabs 0.5 - 2.5 mm<sup>2</sup>

■ Data: brass, tin plated, no EasyEntry.



	mm <sup>2</sup>	Cat. no.	mm d	L	For tabs	s	Pcs/ pack	Rec. tool	Insulation
Red	0,5-1,5	A1507FLSH	3,7	22	6,3x0,8	7	100	GSA0760	PVC*
Blue	1,5-2,5	A2507FLSH	4,3	22	6,3x0,8	8	100	GSA0760	PVC*

s = strip length \* non-brazed with reinforcement sleeve

For detailed information regarding recommended tool, see tool section at the end of this chapter.