

Receptacles with locking lip 0.5 - 6 mm²

■ Data: brass, tin plated.



| mm ² | Cat. no. | mm e | t | L | For tabs | s | Pcs/ pack | Rec. tool |
|-----------------|-----------|------|-----|------|----------|---|-----------|-----------|
| 0,5-1,5 | B1507FLSN | 7,5 | 0,4 | 19,2 | 6,3x0,8 | 7 | 100 | GRB0560 |
| 1,5-2,5 | B2507FLSN | 7,5 | 0,4 | 19,0 | 6,3x0,8 | 8 | 100 | GRB0560 |
| 4-6 | B4607FLSN | 7,5 | 0,4 | 19,0 | 6,3x0,8 | 9 | 100 | GRB0560 |

t = metal thickness s = strip length

Multiple tabs 0.5 - 2.5 mm²

■ Data: brass, tin plated.



| mm ² | Cat. no. | mm e | t | L | For tabs | s | Pcs/ pack | Rec. tool |
|-----------------|-----------|------|-----|------|----------|---|-----------|-----------|
| 0,5-1,5 | B1507FLSH | 8,0 | 0,4 | 20,0 | 6,3x0,8 | 7 | 100 | GRB0560 |
| 1,5-2,5 | B2507FLSH | 8,0 | 0,4 | 20,0 | 6,3x0,8 | 7 | 100 | GRB0560 |

t = metal thickness s = strip length

Receptacle, 90°, 0.5 - 1.5 mm²

■ Data: brass, tin plated.



| mm ² | Cat. no. | mm e | t | L | For tab | s | Pcs/ pack | Rec. tool |
|-----------------|------------|------|-----|------|---------|---|-----------|-----------|
| 0,5-1,5 | B1507FLSB8 | 7,7 | 0,4 | 13,0 | 6,3x0,8 | 7 | 100 | TRB0515B |

t = metal thickness s = strip length

Receptacle 90°, 0.5 - 1 mm²

■ Data: brass, tin plated.



| mm ² | Cat. no. | mm e | t | L | For tabs | s | Pcs/ pack | Rec. tool |
|-----------------|------------|------|-----|-----|----------|---|-----------|-----------|
| 0,5-1 | B1003FLSV5 | 4,9 | 0,3 | 9,3 | 2,8x0,5 | 7 | 100 | DRB0115 |

t = metal thickness s = strip length

For detailed information regarding recommended tool, see tool section at the end of this chapter.