

Ring terminals 0.25 - 6 mm²

■ Data: Cu 99.95%, tin plated, brazed necks.



mm ²	Cat. no.	Screw	mm W	d	t	L	s	Pcs/ pack	Rec. tool
0,25-0,75	B0832R	M3	5,5	1,3	0,5	13,0	7	100	DKB0325
	B0843R	M4	7,5	1,3	0,5	16,2	7	100	DKB0325
	B0853R	M5	9,0	1,3	0,5	17,0	7	100	DKB0325
0,75-1,5	B1532R	M3	5,5	1,8	0,7	13,0	7	100	DKB0325, DKB0760
	B1543R	M4	7,5	1,8	0,7	16,2	7	100	DKB0325, DKB0760
	B1553R	M5	9,0	1,8	0,7	17,0	7	100	DKB0325, DKB0760
	B1565R	M6	11,0	1,8	0,7	20	7	100	DKB0325, DKB0760
	B1585R	M8	14,0	1,8	0,7	23	7	100	DKB0325, DKB0760
	B1510R	M10	17,0	1,8	0,75	26	7	100	DKB0325, DKB0760
1,5-2,5	B2532R	M3	6,0	2,3	0,8	15,0	8	100	DKB0325, DKB0760
	B2537R	M3,5	6,2	2,3	0,8	16,2	8	100	DKB0325, DKB0760
	B2543R	M4	7,5	2,3	0,8	16,2	8	100	DKB0325, DKB0760
	B2553R	M5	9,0	2,3	0,8	17,0	8	100	DKB0325, DKB0760
	B2565R	M6	11,0	2,3	0,8	20	8	100	DKB0325, DKB0760
	B2585R	M8	14,0	2,3	0,8	23	8	100	DKB0325, DKB0760
	B2510R	M10	17,0	2,3	0,75	26	8	100	DKB0325, DKB0760
4-6	B4643R	M4	7,8	3,4	1,0	17,9	9	100	DKB0760
	B4653R	M5	9,0	3,4	1,0	18,0	9	100	DKB0760
	B4665R	M6	11,0	3,4	1,0	20	9	100	DKB0760
	B4685R	M8	14,0	3,4	1,0	23	9	100	DKB0760
	B4610R	M10	17,0	3,4	1,0	27	9	100	DKB0760
	B4613R	M13	18,0	3,7	1,0	30	9	100	DKB0760

t = palm thickness s = strip length

For detailed information regarding recommended tool, see tool section at the end of this chapter.