



## Cable cutting up to Ø 62\* mm



HKS62

Cable cutter.

### Particulars:

- cuts normal types of Cu and Al cables up to Ø 62m
- cuts Al-alloyed AC overhead line conductors up to 241 mm<sup>2</sup> (not ACSR)
- supplied in a robust textile carry bag

Area	Cat. no.	Weight	Length
Ø 62 mm	HKS62	1.9 kg	340 mm

### Cable cutting up to Ø 80\* mm

## HKS80

Cable cutter.

#### Particulars:

- cuts normal types of Cu and Al cables up to Ø 80 mm
- supplied in a robust textile carry bag

Area	Cat. no.	Weight	Length
Ø 80 mm	HKS80	3.4 kg	600 mm

## Cable cutting up to Ø 35\* mm

# HKS35F

Front end cable cutter.

#### Particulars:

- front end "scissors" cutting easy access to confined areas
- cuts normal types of Cu and Al cables up to Ø 35 mm
- Iow handle forces needed
- supplied in a robust textile carry bag

Area	Cat. no.	Weight	Length
Ø 35 mm	HKS35F	1.9 kg	330 mm

HKS35F

HKS80



\* Note! The cutting capacity of any cutting tool may vary due to conductor design, insulation thickness, hardness of materials etc.

