

FSHD23



## FSHD23

Heavy duty leading rod with a knurled recess for effective locking of the earthing wire. For hard and stony soils. To be used with the FSHD11 tip.

Ø	Cat. no.	Weight	Pcs/pack	Length
21 mm	FSHD23	5.5 kg/pack	5	800 mm

FSHD31



## FSHD31

Heavy duty extension rod, with guiding pin that fits into the preceding tube. For hard and stony soils.

Ø	Cat. no.	Weight	Pcs/pack	Length
21 mm	FSHD31	6.2 kg/pack	5	870 mm (incl guiding pin)

FS41 withdrawal handle



## FS41

Withdrawal handle to pull up the top extension rod for re-use. Fits FS and FSHD type rods.

**Particulars:**

- easy to use, with rubber handle grip
- for FS Ø17 and FSHD Ø21 rods

Dimensions hole	Cat. no.	Weight	Pcs/pack	Length x Width
Ø 18,5 mm and Ø 22,5 mm	FS41	0.42 kg	1	230 x 60 mm

FS62C



## FS62C

Driving sleeve used when driving the rods down with a sledge hammer. Must be used to prevent rod end damage.

**Particulars:**

- specially designed for FS21 and FS31 rods

Cat. no.	Weight	Pcs/pack	Length x Width
FS62C	1.0 kg	1	110 x 45 mm

FS61



## FS61

Driving cap used when driving the FS21 and FS31 rods down with a sledge hammer. Used as an alternative to FS62C to prevent rod end damage.

Cat. no.	Weight	Pcs/pack	Length x Width
FS61	0.15 kg	1	58 x 22 mm

FSHD62C



## FSHD62C

Driving sleeve used when driving the FSHD type rods down with a sledge hammer. Must be used to prevent rod end damage.

**Particulars:**

- specially designed for FSHD23 and FSHD31 rods

Cat. no.	Weight	Pcs/pack	Length x Width
FSHD62C	1.0 kg/pack	1	110 x 45 mm