

Power hammer driving studs for Elpress deep earthing system

- specially designed for use with Ø17 mm FS type rods. Studs for use with FSHD rods, contact Elpress
- must be used to protect the rod ends from damage and distortion when power hammers are used
- marked with the catalogue number



| Power Hammer | | Driving tip | | | kg/1 | | |
|--------------|-----------------|-------------|------------|------------------|-----------------|------|------|
| Manufacturer | Type | Cat.no. | Shaft Ø mm | Flange length mm | Total length mm | kg/1 | Note |
| Atlas Copco | BBD 12 TS | FS 71 C | 19 | 108 | 305 | 1,8 | 1 |
| Atlas Copco | BBD 12 T-01 | FS 72 C | 22 | 108 | 305 | 1,9 | 1 |
| Atlas Copco | Cobra 148/248 | FS 72 C | 22 | 108 | 305 | 1,9 | 1 |
| Atlas Copco | Cobra BBM 47 | FS 71 C | 19 | 108 | 305 | 1,8 | 1 |
| Atlas Copco | Pico 20 | FS 72 C | 22 | 108 | 305 | 1,9 | 1 |
| Atlas Copco | RH 571 5L/5LS | FS 72 C | 22 | 108 | 305 | 1,9 | 1 |
| Atlas Copco | RH 658 5L/5LS | FS 72 C | 22 | 108 | 305 | 1,9 | 1 |
| Atlas Copco | TEX 11-DCS | FS 74 C | 22 | 82 | 280 | 1,8 | 1 |
| Atlas Copco | TEX-11-DKS | FS 74 C | 22 | 82 | 280 | 1,8 | 1 |
| Atlas Copco | TEX 23E | FS 73 C | 25 | 108 | 305 | 2,0 | 1 |
| Atlas Copco | TEX 25E | FS 73 C | 25 | 108 | 305 | 2,0 | 1 |
| Atlas Copco | TEX 31/31s | FS 77 C | 32 | 160 | 380 | 2,5 | 1 |
| Atlas Copco | TEX 41/41s | FS 77 C | 32 | 160 | 380 | 2,5 | 1 |
| Berema | Pionjär 120/130 | FS 72 C | 22 | 108 | 305 | 1,9 | 1 |
| Bosch | USH 10 | FS 82 C | 19 | - | 272 | 1,5 | 1 |
| Bosch | USH27 | FS 83 C | 29 | - | 310 | 2,2 | 1 |
| HILTI | TE 52 | FS 81 C | 18 | - | 265 | 1,4 | 1 |
| HILTI | TE72 | FS 81 C | 18 | - | 265 | 1,4 | 1 |
| HILTI | TE 92 | FS 81 C | 18 | - | 265 | 1,4 | 1 |
| HILTI | TE 905/TE805 | FS 88 C | 22 | - | 288 | 1,7 | |
| Hunter | | FS 73 C | 25 | 108 | 305 | 2,0 | 1 |
| Kango | 950 | FS 84 C | 19 | 64 | 289 | 1,5 | 1 |
| Stanley | BR 37 | FS 74 C | 22 | 82 | 280 | 1,8 | 1 |
| Stanley | BR 45 | FS 74 C | 22 | 82 | 280 | 1,8 | 1 |
| Stanley | BR 67 UK | FS 77 C | 32 | 160 | 380 | 2,5 | 1 |
| Stanley | BR 87 UK | FS 77 C | 32 | 160 | 380 | 2,5 | 1 |
| Stanley | DR 19 | FS 74 C | 22 | 82 | 280 | 1,8 | 1 |
| Wacker | BHB 14 | FS 71 C | 19 | 108 | 305 | 1,8 | 1 |
| Wacker | BHB 25 | FS 72 C | 22 | 108 | 305 | 1,9 | 1 |
| Wacker | BHF 25 | FS 85 C | 27 | 80 | 302 | 2,1 | 1 |
| Wacker | BHF 30S | FS 85 C | 27 | 80 | 302 | 2,1 | 1 |
| HILTI/Bosch | SDSMax Syst. | FS 81 D | 18 | - | 215 | 1,4 | |

Note

1. Also available in a HD-version (ex FSHD71C), for FSHD rode with outer diameter 21 mm.