

Tool for stripping of outer conductive layer on MV XLPE cables

FBS1723

Stripping tool for outer vulcanised, conductive layer on MV XLPE cables.

FBS1723



Particulars:

- FBS1723 includes the actual tool, 100 g silicone paste and an instruction, all in a quality plastic carry box
- the tool is easy to use - the tool rotates with the handle.
- stripping can be made from \varnothing 15 mm up to \varnothing 52 mm, approximately corresponding to maximum sizes 50-1000 mm² at 12kV, 25-1000 mm² at 24 kV, 630 mm² at 36 kV and 500 mm² at 52 kV
- cutting depth is easily set between 0 and 15 mm
- unlimited stripping length
- adjustable feed in 5 positions
- blade available as spare part
- the HRC 55 hardness cutting blade is specially ground to specific shape and easy to replace when needed

Area	Cat. no.	Weight	Dimensions
\varnothing 15-52 mm	FBS1723	1.0 kg	275 x 220 x 65 mm
	FBS1723RS (spare blade)		
	FBS1722SP (silicon paste)	0.10 kg	

FBS1723 is delivered in a plastic carry box with silicon paste and instructions for use.

* Note! The cutting capacity of any cutting tool may vary due to conductor design, insulation thickness, hardness of materials etc.