

PRODUCT DATASHEET



Prolab® Patch Panel Labels



This is a multipage document, all pages must be read in conjunction with each other



The Silver Fox Prolab® patch panel self-adhesive labels incorporate a special laser print-receptive surface ensuring the best quality of print every time. The adhesive is acrylic and designed to give long-term bonding. A smooth, clean, dry metal or plastic surface is required.

These labels can be used for a wide range of patch panels that require a self-adhesive label.

Available in packs of 10 or 100 sheets.

TECHNICAL DATA

| | |
|-----------------------------|-------------------------|
| Printing Method | Standard Laser Printer |
| Material | Self-adhesive Polyester |
| Thickness | 50 microns |
| Sheet Size | A4 |
| Standard Colours | See order information |
| RoHS (EU 2002/95/EC) | RoHS Compliant |

FEATURES & BENEFITS

- Print using a standard office laser printer
- Pre-cut for rapid removal from sheet
- Fits a wide range of patch panels

PRODUCT TESTING

| Test | Method |
|--|--|
| Moisture Resistance | MIL-STD-202G Method 106G |
| Low Temperature 72 hours @ -40°C | MIL-STD-810F Method 502.4 |
| High Temperature 2000 hours @ 70°C to 100°C* | MIL-STD-202G Method 108A |
| Hydrogen Sulphide | H ₂ S Sour Gas Exposure (2% H ₂ S) |
| UV Weathering 3000 hours | ISO 4982 Part 3 Method A Cycle 1 |
| Salt Mist Spray | IEC60068-2-52 Test Kb Salt Mist (Cyclic) |

*Samples were subjected to 500 hours @ 70°C, followed by 500 hours @ 85°C followed by 1000 hours @ 100°C

Note: This label is designed for internal use. For external use the user must determine the suitability of this label for their particular application. White material tested for all tests.

etech
components

All Enquiries:

tel: +44 (0)1744 762 929

email: sales@etechcomponents.com

web: www.etechcomponents.com

Copyright © 2015 Silver Fox Limited

R5.4

Page 1 of 2

PRODUCT DATASHEET



Prolab® Patch Panel Labels



This is a multipage document, all pages must be read in conjunction with each other



STORAGE INSTRUCTIONS


| | |
|-----------------------------|---|
| Storage Instructions | Store between 50° F (10° C) and 77° F (25° C) |
| Shelf Life | 2 Years |
| Conditions | Keep in dark conditions |
| Humidity Resistance | 35% to 65% RH |

ORDER INFORMATION

| Product Code | Label Dims (mm) | Labels per Sheet | Sheets per Pack | Labels per Pack | Colour Options |
|--------------|-----------------|------------------|-----------------|-----------------|----------------|
| PATCH4L* | 220 x 9 | 20 | 10 / 100 | 200 / 2000 | |
| PATCH6L* | 126 x 9 | 40 | 10 / 100 | 400 / 4000 | |
| PATCH8L* | 146.5 x 10 | 24 | 10 / 100 | 240 / 24000 | |
| PATCH10L* | 253 x 7 | 22 | 10 / 100 | 220 / 2200 | |

*Specify colour when ordering

SILVER FOX CATALOGUE



TIP - TIME INTO PROFIT BROCHURE



All Enquiries:

tel: +44 (0)1744 762 929

email: sales@etechcomponents.com

web: www.etechcomponents.com

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice.

Copyright © 2015 Silver Fox Limited

R5.4

Page 2 of 2