

PRODUCT DATASHEET



Prolab[®] Asset Labels

**One Software
One Printer
One Ribbon**



This is a multipage document, all pages must be read in conjunction with each other



Silver Fox Prolab[®] Asset Labels are suitable for most asset tagging requirements.

The material is either white or silver polyester with a matt print-receptive topcoat designed for use with the Silver Fox DTP-1 thermal printer and the Silver Fox TSR3 thermal ribbon.

The adhesive is designed to provide excellent adhesion to high and low surface energy plastics, metals, painted metals and powder coatings.

TECHNICAL DATA

Printing Method	Silver Fox DTP-1 Thermal Printer
Thermal Ribbon	Silver Fox TSR3
Material	Self-adhesive Polyester
Thickness	56 microns
Standard Colours	White, Silver
Standard Sizes	60mm x 10mm
RoHS (EU 2002/95/EC)	RoHS Compliant

PRODUCT TESTING

Test	Method
Low Temperature 72 hours @ -40°C	MIL-STD-810F Method 502.4
High Temperature 2000 hours @ 70°C to 100°C*	MIL-STD-202G Method 108A
Hydrogen Sulphide	H ₂ S Sour Gas Exposure (2% H ₂ S)
UV Weathering 2000 hours (Silver)	ISO 4982 Part 3 Method A Cycle 1
UV Weathering 3000 hours (White)	ISO 4982 Part 3 Method A Cycle 1
Salt Mist Spray	IEC60068-2-52 Test Kb Salt Mist (Cyclic)

*Samples were subjected to 500 hours @ 70°C, followed by 500 hours @ 85°C followed by 1000 hours @ 100°C

Note: This label is designed for internal use. For external use the user must determine the suitability of this label for their particular application.

FEATURES & BENEFITS

- Extensively independently tested.
- Same software, same printer, same ribbon for all thermal label types.
- Hi-grade adhesive.

Print using our DTP – 1/300 Thermal Printer.



etech
components

All Enquiries:

tel: +44 (0)1744 762 929

email: sales@etechcomponents.com

web: www.etechcomponents.com

Copyright © 2015 Silver Fox Limited

PRODUCT DATASHEET



Prolab[®] Asset Labels

**One Software
One Printer
One Ribbon**



This is a multipage document, all pages must be read in conjunction with each other



STORAGE INSTRUCTIONS

Storage Instructions	Store between 50° F (10° C) and 77° F (25° C)
Shelf Life	2 Years
Conditions	Keep in dark conditions
Humidity Resistance	35% to 65% RH


ORDER INFORMATION

Product Code	Label Dims (mm)	Labels per Roll	Rolls per Pack	Labels per Pack	Colour Options
P/AT01/5025T**	50 x 25	2500	1	2500	<input type="checkbox"/> <input type="checkbox"/>
P/AT01/6010T**	60 x 10	5000	1	5000	<input type="checkbox"/> <input type="checkbox"/>

**Specify colour when ordering. Please Note: Colours shown are for indicative purposes only – shades may vary.

Use with Silver Fox Labacus Innovator Advanced or Professional software. Print in conjunction with our Fox-in-a-Box Plug'N'Play thermal printer using the same ribbon as all our other thermal labels.

SILVER FOX CATALOGUE



TIP - TIME INTO PROFIT BROCHURE



etech
components

All Enquiries:

tel: +44 (0)1744 762 929

email: sales@etechcomponents.com

web: www.etechcomponents.com

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice.

Copyright © 2015 Silver Fox Limited

R1.1

Page 2 of 2