



# Un-Armored Industrial Gland Non-Explosion Proof Gland (409NP & 494AG series)

SUITABLE FOR UNARMORED CABLES

## Features and benefits:


- For circular, unarmored plastic or rubber sheathed cables
- Large sealing range
- Approved to EN 50262, IEC 62444

## Technical Information:



- Nickel plated brass and aluminum designs
- Suitable for most climatic conditions, weatherproof and waterproof
- 409NP\*\*V – Brass construction with bright autocatalytic nickel coating
- 494AG\*\*V – 6082T6 aluminum construction
- For use in most climatic conditions, rated to IP66 for wet locations

## Specifications

Gland Reference		Cable Dimensions Accommodated			Gland Dimensions			Weight
Design Reference	Hub Size NPT (D)	Overall Jacket Dia. (B)		Hub Length (E)	Protrusion Length (F)	Hexagon		lbs
		Min	Max			A/F (G)	A/C (H)	
409NP-04V	½"	0.315"	0.453"	0.535"	0.87"	0.87"	0.98"	0.19
409NP-08V	¾"	0.433"	0.531"	0.547"	0.87"	0.94"	1.06"	0.19
409NP-14V	1"	0.512"	0.768"	0.689"	0.98"	1.20"	1.34"	0.44
409NP-20V	1¼"	0.748"	1.004"	0.709"	0.98"	1.67"	1.89"	0.76
409NP-27V	1½"	0.984"	1.260"	0.728"	1.30"	1.86"	2.11"	0.63
409NP-31V	2"	1.240"	1.457"	0.768"	1.18"	2.17"	2.36"	0.65
409NP-32V	2"	1.437"	1.693"	0.768"	1.18"	2.22"	2.42"	0.78
409NP-37V	2½"	1.673"	1.969"	0.591"	1.34"	2.76"	3.04"	1.62
409NP-38V	2½"	1.949"	2.165"	1.142"	1.26"	2.95"	3.27"	1.68
409NP-44V	3"	2.146"	2.402"	1.201"	1.26"	3.15"	3.44"	3.57
409NP-45V	3"	2.382"	2.638"	1.201"	1.57"	3.35"	3.74"	3.72
494AG-09V	3"	2.461"	3.071"	1.772"	2.13"	3.90"	4.29"	0.97
494AG-10V	3½"	2.677"	3.465"	1.811"	2.09"	Ø 4.47"	Ø 4.47"	1.21
494AG-11V	4"	3.465"	3.898"	1.850"	2.17"	Ø 4.94"	Ø 4.94"	1.63
494AG-12V	5"	3.898"	4.449"	1.969"	2.24"	Ø 5.94"	Ø 5.94"	3.11
494AG-13V	5"	4.449"	5.039"	1.969"	3.23"	Ø 6.91"	Ø 6.91"	3.80



409NP-



494AG-

