



## **TUBE TERMINAL** **Type KRFS50-300Amm<sup>2</sup>**

Elpress terminals for stranded and flexible conductors acc. to IEC 60228 class 2 and class 5.

Area	bolt	d1	d4	b	d2	a min	e	l	l1	s	Strip length
50	-6	11	14,5	15	6,4	17	1,25	11	40	4	19
	-8	11	14,5	16,5	8,4	17	1,25	11	40	3,8	19
	-10	11	14,5	16,5	10,5	17	1,25	11	41	3,8	19
70	-6	13	17	17	6,4	20	1	11	47	4,5	22
	-8	13	17	17	8,4	20	1	11	47	4,5	22
	-10	13	17	19	10,5	20	1	11	47	3,9	22
95	-6	15	20	19	6,4	23	1	11	52	5,7	25
	-8	15	20	19	8,4	23	1	11	52	5,7	25
	-10	15	20	19	10,5	23	1	11	52	5,7	25
	-12	15	20	20	13	23	1	12	52	5,4	25
120	-6	17	22	19	6,4	25	1	11	56	5,9	27
	-8	17	22	19	8,4	25	1	11	56	5,9	27
	-10	17	22	19	10,5	25	1	11	56	5,9	27
	-12	17	22	22	13	25	1	12	58	5	27
150	-6	19	25	25	6,4	30	1	11	63	6,3	32
	-8	19	25	25	8,4	30	1	11	63	6,3	32
	-10	19	25	25	10,5	30	1	11	63	6,3	32
	-12	19	25	25	13	30	1	12	64	6,3	32
185	-10	21	27	27	10,5	35	1	11	68	6,6	37
	-12	21	27	27	13	35	1	12	70	6,6	37
240A	-10	22,5	29	29	10,5	35	1	15	76	7,7	37
	-12	22,5	29	29	13	35	1	15	76	7,7	37
	-16	22,5	29	29	17	35	1	20	76	7,7	37
300A	-10	24,5	31,5	31	10,5	38	1,25	15	79	8,6	40
	-12	24,5	31,5	31	13	38	1,25	15	79	8,6	40
	-16	24,5	31,5	31	17	38	1,25	20	79	8,6	40