nVent CADDY Pyramid RL Fixed Roller Support







- Roller-based support designed specifically for rooftop applications
- Roller capability allows longitudinal movement of pipe, resulting from thermal expansion or contraction
- Polymeric rollers ensure corrosion free rotation
- Foam bottom offers low abrasion interface for better roof membrane protection
- Compatible with roof surfaces including single ply, bituminous, metal and spray foam
- Ready to use out of the box, saving installation time and labor
- Hot-dip galvanized and UV stabilized for long lasting performance





Material: Polyethylene, Polypropylene, Steel

Finish: Hot-Dip Galvanized Temperature: -45 to 65 °C Static Load Safety Factor: 3:1

Part Number	Article Number	Pipe Size	NB/DN	Height H	Length L	Width W	А	Surface Area	Unit Weight	Static Load F
PRF2	360470	2" Max	50 Max	147 mm	203.0 mm	152 mm	114 mm	26,452 mm²	0.5 kg	440 N
PRF3	360471	3" Max	80 Max	159 mm	317.5 mm	203 mm	159 mm	59,355 mm²	1.0 kg	1,112 N
PRF6	360472	6" Max	150 Max	159 mm	483.0 mm	203 mm	260 mm	91,613 mm²	1.5 kg	2,670 N

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nvent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 nVent All rights reserved nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

