




Cable/Conduit Clip



- Supports conduit to rod, wire or flange
- Can also be used for flexible metallic tubing, armored cable, portable cables, control tubes and communications cable
- Available for EMT, rigid, ENT, IMT, MC/AC and aluminum conduit
- No installation tools required



Material: Spring Steel
Finish: nVent CADDY Armour



| Part Number | Article Number | Outer Diameter OD | Static Load 1 F1 | Static Load 2 F2 | Static Load 3 F3 | Standard Packaging Quantity |
|-------------|----------------|-------------------|------------------|------------------|------------------|-----------------------------|
| KX | 170870 | 12 mm Max | - | - | - | 100 pc |
| K8 | 170660 | 18 mm Max | 220 N | 445 N | 70 N | 100 pc |
| K12 | 170670 | 24 mm Max | 220 N | 445 N | 70 N | 100 pc |
| K12R10 | 191032 | 24 mm Max | 220 N | 445 N | 70 N | 10 x 10 pc |
| K16 | 170680 | 30 mm Max | 220 N | 445 N | 70 N | 100 pc |
| K16R5 | 191038 | 30 mm Max | 220 N | 445 N | 70 N | 10 x 5 pc |
| K20 | 170690 | 42 mm Max | 220 N | 445 N | 100 N | 100 pc |

| Part Number | Outer Diameter | Rod Size |
|-------------|----------------|----------|
| K8 | 8 mm - 18 mm | M4; M6 |
| K12 | 14 mm - 20 mm | M12 |
| K12 | 16 mm - 22 mm | M8; M10 |
| K12 | 18 mm - 24 mm | M4; M6 |
| K16 | 22 mm - 24 mm | M12 |
| K16 | 24 mm - 26 mm | M8; M10 |
| K16 | 26 mm - 30 mm | M4; M6 |
| K20 | 20 mm - 36 mm | M12 |
| K20 | 25 mm - 38 mm | M8; M10 |
| K20 | 30 mm - 42 mm | M4; M6 |
| KX | 4 mm - 12 mm | M4; M6 |

| Part Number | Outer Diameter | Flange Thickness |
|-------------|----------------|------------------|
| K8 | 3 mm - 7 mm | 12 mm - 16 mm |
| K12 | 3 mm - 7 mm | 16 mm - 22 mm |
| K12 | 8 mm - 10 mm | 14 mm - 20 mm |
| K12 | 11 mm - 13 mm | 12 mm - 19 mm |
| K16 | 3 mm - 7 mm | 24 mm - 28 mm |
| K16 | 8 mm - 10 mm | 20 mm - 26 mm |
| K16 | 11 mm - 13 mm | 19 mm - 24 mm |
| K20 | 3 mm - 7 mm | 28 mm - 40 mm |
| K20 | 8 mm - 10 mm | 26 mm - 38 mm |
| K20 | 11 mm - 13 mm | 21 mm - 35 mm |
| KX | 6 mm - 12 mm | 3 mm - 5 mm |

May require dedicated drop wire/rod and EC311. Consult local authority.
For horizontal application only when installing conduit.