

Your representation:

etech
components

All Enquiries:
tel: +44 (0)1744 762 929
email: sales@etechcomponents.com
web: www.etechcomponents.com

FIPJACK®

BCUTP

+450 °C
-75 °C



Abschirmgeflecht
Screening braid



	min.	max.			
Temperaturbereich Temperature range	■	■	■	■	■
Flexibilität/Biegesteifigkeit Flexibility/Ductility	■	■	■	■	■
Dynamik Dynamic	■	■	■	■	■
Mechanischer Schutz Mechanical protection	■	■	■	■	■
Brandverhalten Fire precaution performance	■	■	■	■	■
Chemische Beständigkeit Chemical resistance	■	■	■	■	■
Witterungsbeständigkeit Resistance to weathering	■	■	■	■	■

Material: verzinnete Kupferlitzen

Das Abschirmgeflecht BCUTP mit verzinneten Kupferlitzen aus der FIPJACK® Produktereihe eignet sich besonders zur Abschirmung von Kabeln und Leitern hinsichtlich elektromagnetischer Verträglichkeit (EMV). Das speziell hergestellte Geflecht mit einer Überdeckung von 90 – 95% bietet sehr gute Schirmwerte für industrielle Anlagen und Geräte.

Material: tin-plated copper

This FIPJACK® tin plated copper braid type BCUTP offers effective screening protection of cables and wires regarding electromagnetic compatibility (EMC). This special braid offers a coverage of 90 – 95% and is especially suited for very good screening effectiveness for industrial equipment and plant engineering.



Artikel-Nr. Part No.	Nennweite Nominal width	Einsatzbereich Range of application		Spezifikation Specification	Gewicht in kg Weight in kg	VPE PU
schwarz / black	NW	D _{min} in mm	D _{max} in mm		pro 100 m / per 100 m	m
BCUTP-03S90.100	03	2,0	3,5	16 x 7 x 0,13	1,00	100
BCUTP-04S90.100	04	3,0	5,0	16 x 7 x 0,13	1,40	100
BCUTP-06S90.100	06	4,5	7,0	24 x 7 x 0,13	2,05	100
BCUTP-10S90.100	10	7,0	12,0	24 x 9 x 0,16	4,35	100
BCUTP-12S90.100	12	11,0	13,0	24 x 10 x 0,16	4,80	100
BCUTP-15S90.100	15	13,0	18,0	24 x 11 x 0,20	8,20	100
BCUTP-20S95.50	20	16,0	38,0	48 x 16 x 0,13	9,50	50
BCUTP-25S95.50	25	22,0	38,0	48 x 18 x 0,16	17,30	50
BCUTP-30S95.50	30	27,0	40,0	48 x 20 x 0,16	19,30	50
BCUTP-35S95.50	35	30,0	50,0	48 x 20 x 0,16	19,50	50
BCUTP-40S95.50	40	35,0	60,0	48 x 18 x 0,20	27,00	50
BCUTP-50S95.25	50	45,0	65,0	36 x 14 x 0,30	35,00	25*

*Nennweite 50 wird ohne PVC Stützschauch geliefert. / Size 50 is supplied without PVC former tube.

