

Your representation:

etech
components

All Enquiries:
tel: +44 (0)1744 762 929
email: sales@etechcomponents.com
web: www.etechcomponents.com

EURO
2000

FIP METAL®

DMC-PU

Metallschlauch
Metal conduit

+120 °C
-45 °C



	min.					max.
Temperaturbereich Temperature range						
Dynamik Dynamic						
Mechanischer Schutz Mechanical protection						
Brandverhalten Fire precaution performance						
Chemische Beständigkeit Chemical resistance						

Material: Stahl verzinkt, TPU ummantelt

Der flexible Kabelschuttschlauch DMC-PU aus verzinktem Stahl und mit einer spezieller Verklammerung, ist von einer verstärkten, glatten Polyurethanschicht ummantelt. Diese ist halogenfrei und schützt effektiv gegen Traktion, Torsion und Stauchung. DMC-PU ist in vielen industriellen Anwendungen einsetzbar.

Material: Galvanized steel, TPU full coated

The flexible galvanized carbon steel conduit DMC-PU with special seam is surrounded by a smooth polyurethane jacket. This is halogen free and gives extra protection against traction, torsion and compression. DMC-PU can be applied in many industrial applications.



Artikel-Nr. Part No.		Nennweite Nominal width	Gewicht Weight	Dimensionen in mm (nom.) Dimensions in mm (nom.)		Biegeradius Bending radius	Rollenlänge Reel length
FIP	EURO 2000	NW	+/- 4% gr/mt	ID	AD / OD	mm	m
MC-DMC-210-PU.30	DMC-210-PU	10	251	10,0	15,5	50	30
MC-DMC-212-PU.30	DMC-212-PU	12	295	12,0	18,0	60	30
MC-DMC-216-PU.30	DMC-216-PU	15,5	384	15,5	21,5	70	30
MC-DMC-221-PU.30	DMC-221-PU	20,5	527	20,5	27,0	90	30
MC-DMC-227-PU.30	DMC-227-PU	26,5	685	26,5	33,0	120	30
MC-DMC-235-PU.30	DMC-235-PU	34,5	888	34,5	43,0	150	30
MC-DMC-240-PU.25	DMC-240-PU	39,5	952	39,5	48,0	200	25
MC-DMC-250-PU.25	DMC-250-PU	50,5	1378	50,5	60,0	250	25

DMC-PU Metallschutzschläuche sind mit Dichtring AB zu kombinieren. Weitere Informationen erhalten Sie auf Seite 152.

DMC-PU metal conduits have to use with seal ring AB. More information may be found on page 152.

