

Tube terminals 10 - 1000 mm², KRT

- Data: electrolytic copper, tin plated.
- Cable inspection hole, for stranded (class 2) Cu-conductors.
- UL-approved (KRT 10-500 mm²). DNV-approved (KRT 10-400 mm²).

Marking example KRT: 70 10 (Elpress logotype included)

70 = mm²

10 = palm hole for M10



AWG	Cat. no.	mm W	d	N	N ₁	L	Pcs/ pack	Die no.	Rec. tool
8	KRT10-5	10	4,5	6	8	29	100	7	V600, V1300
8	KRT10-6	10	4,5	6	8	29	100	7	V600, V1300
8	KRT10-8	13	4,5	8	11	34	100	7	V600, V1300
8	KRT10-10	16	4,5	8	11	34	100	7	V600, V1300
8	KRT10-12	19	4,5	10	14	41	100	7	V600, V1300
6	KRT16-5	12	5,5	6	8	34	100	8,5	V600, V1300
6	KRT16-6	12	5,5	6	8	34	100	8,5	V600, V1300
6	KRT16-8	15	5,5	8	11	39	100	8,5	V600, V1300
6	KRT16-10	16	5,5	8	11	39	100	8,5	V600, V1300
6	KRT16-12	19	5,5	10	15	47	100	8,5	V600, V1300
4	KRT25-6	14	7	9	12	43	100	10	V600, V1300
4	KRT25-8	15	7	9	12	43	100	10	V600, V1300
4	KRT25-10	16	7	9	12	43	100	10	V600, V1300
4	KRT25-12	19	7	12	13	48	100	10	V600, V1300
2	KRT35-6	17	8,5	9,5	11,5	49	100	12	V600, V1300
2	KRT35-8	17	8,5	9,5	11,5	49	100	12	V600, V1300
2	KRT35-10	19	8,5	9,5	11,5	49	100	12	V600, V1300
2	KRT35-12	22	8,5	12	14	53	100	12	V600, V1300
1/0	KRT50-6	20	10	11	12	53	100	14	V600, V1300
1/0	KRT50-8	20	10	11	12	53	100	14	V600, V1300
1/0	KRT50-10	20	10	11	12	53	100	14	V600, V1300
1/0	KRT50-12	22	10	12	14	56	100	14	V600, V1300
2/0	KRT70-8	23	12	11	12	55	100	16	V600, V1300
2/0	KRT70-10	23	12	11	12	55	100	16	V600, V1300
2/0	KRT70-12	23	12	12	14	58	100	16	V600, V1300
4/0	KRT95-8	26	13,5	11	12	60	100	18	V600, V1300
4/0	KRT95-10	26	13,5	11	12	60	100	18	V600, V1300
4/0	KRT95-12	26	13,5	12	14	63	100	18	V600, V1300
4/0	KRT95-16	28	13,5	15	17	69	100	18	V600, V1300
250	KRT120-10	28	15	11	14	64	100	19	V1300, V250
250	KRT120-12	28	15	12	14	64	100	19	V1300, V250
250	KRT120-16	28	15	15	17	70	100	19	V1300, V250
300	KRT150-12	32	17	15	17	76	50	22	V1300, V250
300	KRT150-16	32	17	15	17	76	50	22	V1300, V250
300	KRT150-20	32	17	19	20	83	50	22	V1300, V250
350	KRT185-12	35	19	15	17	79	50	24	V1300, V250
350	KRT185-16	35	19	15	17	79	50	24	V1300, V250
350	KRT185-20	35	19	19	20	86	50	24	V1300, V250
500	KRT240-12	38	21	15	17	86	50	26	V1300, V250
500	KRT240-16	38	21	15	17	86	50	26	V1300, V250
500	KRT240-20	38	21	19	20	93	50	26	V1300, V250
600	KRT300-12	44	24	19	20	100	25	30	V1300, V250
600	KRT300-16	44	24	19	20	100	25	30	V1300, V250
600	KRT300-20	44	24	19	20	100	25	30	V1300, V250

** total palm length

Table continue on next page. →

For detailed information regarding recommended tool or system, see chapter 6.

Cu terminals and connectors 0.75 - 1000 mm²

AWG	Cat. no.	mm W	d	N	N ₁	L	Pcs/ pack	Die no.	Rec. tool
750	KRT400-16	48	26	21	31	114	25	32	V1300, V250
750	KRT400-20	48	26	21	31	114	25	32	V1300, V250
750	KRT400-24	48	26	21	31	114	25	32	V1300, V250
1000	KRT500-00	58	31	70**	-	160	-	40	V250
1000	KRT500-16	58	31	25	35	150	-	40	V250
1000	KRT500-20	58	31	25	35	150	-	40	V250
1000	KRT500-24	58	31	25	35	150	-	40	V250
	KRT630-00	65	34	70**	-	160	-	45	V250
	KRT630-20	65	34	25	35	150	-	45	V250
	KRT630-24	65	34	25	35	150	-	45	V250
	KRT800-00	75	39	80**	-	195	-	53	V250
	KRT800-24	75	39	35	45	195	-	53	V250
	KRT1000-00	80	43	80**	-	195	-	56	V1470

** total palm length

For detailed information regarding recommended tool or system, see chapter 6.