

MC52i / MC55i Terminal



Quad-Band 2G



TCP/IP



GPRS
Class 10



FAX Functionality



e-mark



RIL Driver



Full Voice
Support



Extended
Temperature
Range



2G

Cinterion® MC52i / MC55i Terminals
GPRS Connectivity in a Box

Cinterion® MC52i / MC55i Terminals

GPRS Connectivity in a Box

Following up the successful TC35i/MC35i Terminals, the new generation of GPRS Terminals is available. Based on the powerful MC55i wireless module platform the improved Terminals offer additional functionality while remaining compatible with its predecessors.

MC55i Terminal packs a Quad-Band GSM/GPRS baseband with TCP/IP connectivity based on GPRS Class 10 data transmission into a compact plug-and-play housing. The robust housing includes a range of common interfaces as well as an integrated SIM cardholder which make the new generation to an all-in-one solution enabling voice, data, SMS

and fax communication. The new generation is available as Quad-Band with GPRS Class 10 functionality (MC55iT) and as a Dual-Band variant with GPRS Class 8 functionality (MC52iT). With an extended temperature range, the reliable terminals can be used in a wide range of M2M business fields such as metering, remote maintenance, traffic systems, transportation and logistics, and security.

Like all Cinterion products, MC52iT / MC55iT come with full type approval (FTA) and are certified according to automotive e-mark as well as by the largest carriers worldwide.

GPRS Connectivity in a Box



TCP/IP

The integrated TCP/IP stack enables the application to send and receive packed data. This means there is no additional protocol on the micro-controller of the application required to ensure point-to-point communication based on AT commands within the global data network. Both terminals also support transparent mode that is more efficient for small data packets.

GPRS Class 10

General Packet Radio Services (GPRS) enhancing 2G terminals to ensure "always on" communication at high speed. MC55iT supports GPRS Class 10 with a maximum data rate of 86 kbps in download and 42.8 kbps in upload.

Gemalto M2M Support includes:

- > Personal design-in consulting for hardware and software
- > Extensive RF test capabilities
- > GCF/PTCRB conform pretests to validate approval readiness
- > Regular training workshops



Local engineers, a competent helpdesk, a dedicated team of R&D specialists and an advanced development center are the hallmarks of our leading support offer.

Cinterion® MC52i / MC55i Terminals Features

GENERAL FEATURES

- > GSM Quad-Band 850 / 900 / 1800 / 1900 MHz (MC55iT)
- > GSM Dual-Band 900 / 1800 MHz (MC52iT)
- > 3GPP Release 98
- > GPRS multi-slot Class 10/8
- > Compliant to GSM phase 2/2+
- > Output power:
 - > Class 4 (2W) for GSM850
 - > Class 4 (2W) for GSM900
 - > Class 1 (1W) for GSM1800
 - > Class 1 (1W) for GSM1900
- > SIM Application Toolkit
- > Control via AT commands (Hayes, 3GPP TS 27.007 and 27.005)
- > TCP/IP stack access via AT commands
- > Internet Services TCP server/client, UDP, ICMP, DNS, HTTP, FTP, SMTP, POP3
- > Supply voltage range: 8 – 30 V
- > Operating temperature: -30 °C to +75 °C
- > Dimensions: 65 × 74 × 33 mm
- > Weight: 110 g
- > WEEE
- > RoHS and EuP compliant

SPECIFICATIONS

- > GPRS Class 10/8,
 - DL: max. 85.6 kbps
 - UL: max. 42.8 kbps (MC55iT)
 - UL: max. 21.4 kbps (MC52iT)
 - Mobile Station Class B
- > CSD data transmission up to 14.4 kbps, V.110, non-transparent
- > USSD support
- > SMS text and PDU mode, cell broadcast
- > Fax group 3, Class 1 and Class 2
- > High quality voice support
- > Handsfree operation
- > FR, HR, EFR and AMR speech codec support
- > Integrated TTY modem

SPECIAL FEATURES

- > Firmware update via serial interface
- > Real time clock with alarm functionality

INTERFACES

- > Antenna connector FME (male)
- > Plug-in power supply connector (6-pole Western jack)
- > Handset analog audio interface (4-pole Western jack)
- > Mini-SIM card reader, 1.8 V and 3.0 V
- > V.24 / V.28 RS-232 interface (D-sub 9-pole female socket)
- > Operating status LED

DRIVERS

- > Serial interface modem driver for Microsoft® Windows 7™, Windows XP™ and Windows Vista™ (MC55iT)
- > RIL driver Windows Mobile 6

APPROVALS

- > Local approvals and network operator certifications
- > CE, R&TTE, GCF, FCC, PTCRB, IC, e-mark

For more information, please visit

m2m.gemalto.com, www.facebook.com/gemalto, or Follow @gemaltom2m on twitter.

The information provided in this brochure contains merely general descriptions or characteristics of performance, which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract. All product designations may be trademarks or product names of Cinterion Wireless Modules GmbH or supplier companies whose use by third parties for their own purposes could violate the rights of the owners. Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners. ARM9 is a registered trademark of ARM Limited.

Gemalto M2M GmbH
St.-Martin-Str. 60
81541 Munich
Germany



➔ M2M.GEMALTO.COM

gemalto 
security to be free