



TAPCON CSK





PRODUCT DESCRIPTION

• Self tapping screw with countersunk head for fastening into cracked & non -cracked concrete

PRODUCT PROMISE

ETA Approved, fire rated, industry leading high performance concrete anchor

FEATURES AND BENEFITS

- Complete range ETA Option 1 can be used in cracked & non -cracked concrete
- Fire approval
- Longer effective thread allows highest performance within the market
- New patented thread design provides easy setting
- Adjustable anchor for alignment situations when required without loss of performance
- Large choice of drilling diameters & lengths
- 3 anchoring depths for Ø6 & Ø8

APPROVALS









APPLICATIONS

- TrunkingHanging Services From Ceiling or From Walls
- Walls
 Suspended Ceiling
 Temporary fixings
 Scaffolding
 Road Signs
 Safety Barriers
 Stadium Seating
 Pallet Racking
 M&E
 Cable travs

- Cable traysWindow FramesRailingsHVAC

SUBSTRATES







PRODUCT RANGE

40 mm						
	40 mm	35 mm	5 mm	TX 25	100	058770
60 mm	40 mm	35 mm	15 mm	TX 25	100	058771
40 mm	40 mm	35 mm	5 mm	TX 30	100	058772
60 mm	40 mm	35 mm	15 mm	TX 30	100	058773
80 mm	40 mm	35 mm	25 mm	TX 30	100	058774
100 mm	40 mm	35 mm	45 mm	TX 30	100	058775
120 mm	40 mm	35 mm	65 mm	TX 30	100	058776
140 mm	40 mm	35 mm	85 mm	TX 30	100	058777
	40 mm 60 mm 80 mm 100 mm	40 mm 40 mm 60 mm 40 mm 80 mm 40 mm 100 mm 40 mm 120 mm 40 mm	40 mm 40 mm 35 mm 60 mm 40 mm 35 mm 80 mm 40 mm 35 mm 100 mm 40 mm 35 mm 120 mm 40 mm 35 mm	40 mm 40 mm 35 mm 5 mm 60 mm 40 mm 35 mm 15 mm 80 mm 40 mm 35 mm 25 mm 100 mm 40 mm 35 mm 45 mm 120 mm 40 mm 35 mm 65 mm	40 mm 40 mm 35 mm 5 mm TX 30 60 mm 40 mm 35 mm 15 mm TX 30 80 mm 40 mm 35 mm 25 mm TX 30 100 mm 40 mm 35 mm 45 mm TX 30 120 mm 40 mm 35 mm 65 mm TX 30	40 mm 40 mm 35 mm 5 mm TX 30 100 60 mm 40 mm 35 mm 15 mm TX 30 100 80 mm 40 mm 35 mm 25 mm TX 30 100 100 mm 40 mm 35 mm 45 mm TX 30 100 120 mm 40 mm 35 mm 65 mm TX 30 100