



TAPCON CSK XTREM





PRODUCT DESCRIPTION

• Self tapping screw with countersunk head for fastening into cracked & non -cracked concrete & for seismic applications

PRODUCT PROMISE

ETA Seismic Approved, fire rated, industry leading high performance concrete anchor

FEATURES AND BENEFITS

- Complete range ETA Option 1 can be used in cracked & non -cracked concrete
- TAPCON XTREM range which can be used in C1 seismic zones
- Fire approval
- Longer effective thread allows highest performance within the market
- New patented thread design provides easy setting
- Adjustable anchor for alignment situations when required without loss of performance
- Large choice of drilling diameters & lengths
- 3 anchoring depths for Ø6

APPROVALS













APPLICATIONS

- TrunkingHanging Services From Ceiling or From
- Valls
 Suspended Ceiling
 Temporary fixings
 Scaffolding
 Road Signs
 Safety Barriers
 Stadium Seating
 Pollet Packing

- Pallet RackingM&E
- Cable trays
- Window Frames
- RailingsHVAC

SUBSTRATES





PRODUCT RANGE

Diameter Anchor ▲▼ A	Anchor Length ▲▼	Min. Drilling Depth ▲▼	Min. Embedment Depth ▲▼	Max. Fixing Thickness ▲▼	Recess Size ▲▼	Quantity ▲▼	Product Code ▲▼
8 mm 8	30 mm	55 mm	45 mm	35 mm	TX 40	50	058778

