



TAPCON CSK XTREM A4





PRODUCT DESCRIPTION

 Stainless steel self tapping screw with countersunk head for fastening into cracked & non -cracked concrete & for seismic applications

PRODUCT PROMISE

ETA Seismic Approved, fire rated, industry leading high performance concrete anchor

FEATURES AND BENEFITS

- Complete range ETA Option 1 can be used in cracked & non -cracked concrete
- TAPCON XTREM range which can be used in C1 seismic zones
- Fire approval
- Stainless steel anchor for external conditions
- Adjustable anchor for alignment situations when required without loss of performance
- 3 anchoring depths for Ø8 & 10

APPROVALS















APPLICATIONS

- TrunkingHanging Services From Ceiling or From Walls

- Road SignsSafety BarriersStadium Seating
- M&E
- Cable traysWindow Frames
- RailingsHVAC
- Facades
- Canopies
- Balconies

SUBSTRATES





PRODUCT RANGE

Diameter Anchor ▲▼	Anchor Length ▲▼	Min. Drilling Depth ▲▼	Min. Embedment Depth ▲▼	Max. Fixing Thickness ▲▼	Recess Size ▲▼	Quantity ▲▼	Product Code ▲▼
8 mm	80 mm	55 mm	45 mm	35 mm	TX 40	50	058814
10 mm	90 mm	65 mm	55 mm	35 mm	TX 50	50	058815

