

## TAPCON HFL

**spit**



### PRODUCT DESCRIPTION

- Self tapping screw with hexagonal head for fastening into cracked & non -cracked concrete

### PRODUCT PROMISE

High performance concrete undercut anchor screw, that reduces installation time and edge and spacing distance

### FEATURES AND BENEFITS

- ETA Option 1 approved anchor for cracked & non -cracked concrete
- Fire approval
- Longer effective thread allows highest performance within the market
- New patented thread design provides easy setting
- Adjustable anchor for re-alignment without loss of performance
- Removable anchor allows for temporary fixings
- Large choice of drilling diameters, heads & lengths

### APPROVALS



## APPLICATIONS

- Formwork
- Mechanical and electrical
- Façade and curtain walls
- Demolition
- Safety barriers and hand rails
- Security gates and fencing
- Racking and storage
- Machinery and equipment
- Stadium seating
- Signage and lighting
- Infrastructure - energy, road, rail
- HVAC

## SUBSTRATES



## PRODUCT RANGE

Diameter Anchor ▲▼	Anchor Length ▲▼	Min. Drilling Depth ▲▼	Min. Embedment Depth ▲▼	Max. Fixing Thickness ▲▼	Quantity ▲▼	Product Code ▲▼
5 mm	40 mm	40 mm	35 mm	5 mm	100	058726
5 mm	50 mm	40 mm	35 mm	15 mm	100	058727
5 mm	60 mm	40 mm	35 mm	25 mm	100	058728
6 mm	40 mm	40 mm	35 mm	5 mm	100	058729
6 mm	50 mm	40 mm	35 mm	15 mm	100	058730
6 mm	80 mm	40 mm	35 mm	45 mm	100	058731
6 mm	100 mm	40 mm	35 mm	65 mm	100	058732