

TAPCON HFL XTREM A4

spit



PRODUCT DESCRIPTION

- Stainless steel self tapping screw with hexagonal head for fastening into cracked & non -cracked concrete & for seismic applications

PRODUCT PROMISE

Stainless steel, ETA and seismic application approved concrete anchor screw, that reduces installation time and edge and spacing distance

FEATURES AND BENEFITS

- ETA Option 1 approved anchor for cracked & non -cracked concrete
- Stainless steel A4 anchor for external applications
- TAPCON XTREM range approved for C1 seismic applications
- Fire approval
- Longer effective thread allows highest performance within the market
- New patented thread design provides easy setting
- 500hrs salt spray zinc flake coating
- Adjustable anchor for re-alignment without loss of performance
- Removable anchor allows for temporary fixings


APPROVALS



APPLICATIONS

- Formwork
- Mechanical and electrical
- Façade and curtain walls
- Demolition
- Safety barriers and hand rails
- Security gates and fencing
- Racking and storage
- Machinery and equipment
- Stadium seating
- Signage and lighting
- Infrastructure, energy/road/rail
- HVAC

SUBSTRATES



PRODUCT RANGE

Diameter Anchor ▲▼	Anchor Length ▲▼	Min. Drilling Depth ▲▼	Min. Embedment Depth ▲▼	Max. Fixing Thickness ▲▼	Quantity ▲▼	Product Code ▲▼
8 mm	70 mm	55 mm	45 mm	25 mm	50	058809
8 mm	80 mm	55 mm	45 mm	35 mm	50	058810
10 mm	90 mm	65 mm	55 mm	35 mm	50	058811
10 mm	100 mm	65 mm	55 mm	45 mm	50	058812
10 mm	120 mm	65 mm	55 mm	65 mm	50	058813