

Cu terminals and connectors 0.75 - 1000 mm²

Cu terminals 50 - 240 mm², KRFN, with narrow palm

- Data: electrolytic copper, tin plated.
- Cable inspection hole, for stranded (class 2) and flexible (class 5) Cu-conductors.
- Easy to mount through conduits, enables pre-assembly.

Marking example KRF: 70 10F (Elpress logotype included)

70 = mm² 10 = palm hole for M10 F = type KRF, for stranded and flexible conductors



Cat. no. mm ² , Bolt	mm W	d	D	N	N ₁	L ₁	L	Pcs/Pack	Die no.	Rec. tool
KRFN50-6	18	11	14,5	11	11	40	51	100	14,5	V600, V1300
KRFN50-8	18	11	14,5	11	11,5	40	51	100	14,5	V600, V1300
KRFN50-10	18	11	14,5	11	11,5	40	51	100	14,5	V600, V1300
KRFN70-6	20	13,0	17,0	11	11,5	45	56	50	14,5	V600, V1300
KRFN70-8	20	13,0	17,0	11	11,5	45	56	50	17	V600, V1300
KRFN70-10	20	13,0	17,0	11	11,5	45	56	50	17	V600, V1300
KRFN95-8	24	15,0	20,0	11	12	50	61	50	20	V600, V1300
KRFN95-10	24	15,0	20,0	11	13	51	62	50	20	V600, V1300
KRFN95-12	24	15,0	20,0	12	14	52	64	50	20	V600, V1300
KRFN120-8	26	17,0	22,0	11	12	54	65	50	22	V1300, V250
KRFN120-10	26	17,0	22,0	11	13	55	66	50	22	V1300, V250
KRFN120-12	26	17,0	22,0	12	14	56	68	50	22	V1300, V250
KRFN150-10	30	19,0	25,0	11	13	62	73	50	25	V1300, V250
KRFN150-12	30	19,0	25,0	12	14	63	75	50	25	V1300, V250
KRFN185-10	32	21,0	27,0	11	14	69	80	25	27	V1300, V250
KRFN185-12	32	21,0	27,0	12	15	70	82	25	27	V1300, V250
KRFN185-16	32	21,0	27,0	15	16	71	86	25	27	V1300, V250
KRFN240A-10	38	22,5	29,0	11	16	73	84	50	30	V1300, V250
KRFN240A-12	38	22,5	29,0	12	15	72	84	50	30	V1300, V250
KRFN240A-16	38	22,5	29,0	15	18	75	90	50	30	V1300, V250



KRFN terminals suitable for narrow spaces.



Easy to mount through conduits.

For detailed information regarding recommended tool or system, see chapter 6.