



HKL40/KL40, HKL55/KL55, HKL85/KL85

A series of cable cutters covering almost all needs when cutting power cables and lines. The cutter heads (KL) are operated with one of Elpress' pumps, e.g. foot pump P4000 or pump PS710. Not for steel wire and wire reinforced cable.



Max ϕ conductor	Name	Net weight (kg)	Length	Width	Height
40	HKL40	6,058	645	165	85
55	HKL55	4,133	560	140	55
85	HKL85	7,6	745	190	72
40	KL40	4,7	285	105	85
55	KL55	3,5	300	110	55
85	KL85	6,7	385	170	75

HKL40, KL40. HKL55 and KL55

Do not cut wire reinforced cable.



HKL85 and KL85

Technical Specifications

HKL40/KL40/HKL55/KL55/HKL85/KL85

Hydraulic manual cutters	HKL40	HKL55	HKL85
Hydraulic cutting heads	KL40	KL55	KL85
Max. opening	ϕ 40	ϕ 55	ϕ 85
Max. cutting force, KN	88	43	55
Max. cutting capacity, examples.			
copper cable	ϕ 40	400 (500) mm ²	630 mm ²
Cu annealed solid conductor		ϕ 20	
Cu rod	ϕ 30		
Aluminium cable	ϕ 40	3x240+95 mm ²	3x240+95 mm ² 630 (800 mm ²)
Al annealed solid conductor		ϕ 25	
ACSR	ϕ 40		
Al bar	ϕ 40		
Telephone cable		ϕ 55	
Steel wire (<180daN/mm ²)	ϕ 11		
Steel rod	ϕ 18		