

# Tools for Cu terminals 10 - 800 mm<sup>2</sup>, Al terminals 16 - 630 mm<sup>2</sup> and C-sleeves 6 - 300 mm<sup>2</sup>



## V250



Tested and certified crimp head for crimping Cu-terminals, type KR/KRT 10 mm<sup>2</sup>, KS/KST 10 mm<sup>2</sup>, KRF/KRD/KRT 16-800 mm<sup>2</sup>, KSF/KSD/KST 16-800 mm<sup>2</sup>, Al-terminals 16-630 mm<sup>2</sup> (-300 solid), C sleeves 6/6-300/300 mm<sup>2</sup>. Used in combination with foot pump P4000 or the electrically powered pump PS710 (battery powered version of PS710E is also available).

### Properties:

- working pressure 63 MPa (630 bar)
- crimp force 250kN (25 tonnes)
- large crimp area, 10-800 mm<sup>2</sup>

mm <sup>2</sup> (Cu)	mm <sup>2</sup> (Stranded Al)	mm <sup>2</sup> (Solid Al)	Name	Crimp geometries	Net weight (kg)	Length mm	Width	Height
10-800	16-630	16-300	V250	Punch, Hexagonal, Oval	4,68	280	111	74

### Crimp geometries

