



A2EXP Ex d IIC / Ex e II Dual Seal Cable Gland (495AB Series)

SUITABLE FOR USE WITH CIRCULAR UNARMoured & BRAIDED CABLES

Features and benefits:

- Brass indoor and outdoor cable gland for use in hazardous areas
- Suitable for circular Unarmoured cables with extruded oversheath
- Fitted with silicone rubber low smoke, zero halogen seal
- Achieves IP66, IP68 (1 bar) and deluge proof (DTS01:1991) seal onto cable and to enclosure with suitable sealing washer or thread sealant
- Suitable for most climatic conditions – weatherproof, waterproof and deluge proof
- Standard and Nickel plated versions available
- Full Installation Instructions supplied

Technical Information:

Certified II 2GD, Ex e II & Ex d IIC under ATEX directive 94/9/EC
Atex Compliance Standards: EN 60079-0, EN 60079-1, EN 60079-7,
EN 61241-0, EN 61241-1

Certificate number Sira99ATEX1086X

IECEX Compliance Standards: IEC 60079-0, IEC 60079-1, IEC 60079-7,
IEC 61241-0, IEC 61241-1

Certificate number IECEX SIR 10.0069X

Service temperature range -50°C to +200°C

UL Classified in accordance with IEC 60079-0, 60079-1 and 60079-7 for use
in hazardous locations

UL Listed for use in Class 1, Zone 0, 1 and 2 hazardous locations for Canada

Specifications

Gland Reference		Cable Dimensions mm			Gland Dimensions mm				
Design Reference		Size	Cable Diameter Ø (B) mm		Entry Thread (D)	Thread Length (E)	Protrusion Length (F)	Hexagon	
Standard	Nickel Plated		Min	Max				A/F (G)	A/C (H)
495AB-51	495AB-51V	16	3.5	8.5	M16×1.5	15	65	22	24.9
495AB-71	495AB-71V	20SS	3.5	8.5	M20×1.5	15	65	22	24.9
495AB-52	495AB-52V	20S	8.0	11.5	M20×1.5	15	62	22	24.9
495AB-53	495AB-53V	20	8.0	16.0	M20×1.5	15	81	25.7	28.7
495AB-55	495AB-55V	25	11.5	21.0	M25×1.5	15	85	33	36.9
495AB-56	495AB-56V	32	18.5	27.5	M32×1.5	15	69	37.5	42.2
495AB-57	495AB-57V	40	24.0	34.0	M40×1.5	15	82	47.2	53.6
495AB-59	495AB-59V	50	31.0	41.0	M50×1.5	15	79	56.4	61.5
495AB-61	495AB-61V	63	40.0	52.5	M63×1.5	15	113.5	70	77.2
495AB-62	495AB-62V	75S	52.5	58.0	M75×1.5	15	78.5	80	87.4
495AB-63	495AB-63V	75	54.5	65.5	M75×1.5	15	120	80	87.4

Sizes 75s and 75 shall only be used for fixed installations.

In addition the user / installer should ensure that the cables are adequately clamped.

