



Hook Cleat (Aluminium) 371 series

- Suitable for use with cable diameters 19 to 76mm.
- Manufactured from aluminium alloy.
- Self-adjusting ranges.
- Two-piece, single fixing design.
- Can be double stacked on a single fixing.
- Can be installed in temporary open position to aid single person working.
- Suitable for indoor dry normal industrial use or outdoor unpolluted areas.
- Operating temperature -60°C to +105°C.
- Not designed to secure cables in long vertical routes.
- LUL approved product register ID 1962.

SINGLE WAY CLEATS

Technical Data

Cable and Cleat Selection			Cleat Details							
Design Number	Cable diameter		Dimensions (mm)							Weight (g)
	A (mm)		B		C	D	E	F	G	
	Min	Max	Min	Max						
371AA03	19	22	29	33	57	38	24	19	57	
371AA04	22	25	34	37	62	38	26	19	71	
371AA05	25	32	37	45	74	45	29	24	106	
371AA06	32	38	44	50	81	45	32	24	113	
371AA07	38	44	50	57	88	45	35	24	142	
371AA08	44	51	55	63	94	45	38	24	142	
371AA09	51	57	64	72	103	45	43	24	191	
371AA10	57	64	72	79	111	45	48	24	213	
371AA11	64	70	80	91	124	45	53	25	291	
371AA12	70	76	91	96	132	45	57	27	326	

Method of Fixing

In all applications the cleat should be mounted on suitable M10 fixings.

When mounting directly on "Unistrut" or "Leprack" type channel, adaptor plate 380AC02 should be used (please see page 39).

Performance Data

Test Standard	EN 50368:2003
Type	6.1.1 Metallic
Impact Resistance	6.2.5 V. Heavy
Lateral Load	1.32 -> 1.5 kN
Axial Load	82 -> 109 N
Needle Flame	>120 secs

* Technical Information subject to change without notice

