


SPIT PULSA 40E



+ Pulsa E-Lift pole tool

In accordance to:
 EN 12549
 EN ISO 11148-13
 Directive tool :
 2006/42/EC
 2011/65/UE
 1999/5/EC
 CEM 2004/108/EC
 Fuel cell : 75/324/EC
 Battery : 2006/66/EC
 Charger :
 2006/95/EC
 CEM 2004/108/EC

Tool Specifications	
Name	SPIT PULSA 40E
Impact force (Joules)	82
Weight (kg)	3.7 kg (with battery)
Overall dimension LxHxH (mm)	399x113x309
Energy	Fuel cell & Battery
Fastener lengths (mm)	15 to 40 mm in strip

Characteristics
Electrical accessories pin-guide
Fully automatic tool (1000 shots per hour)
20 pins magazine (10 per strip)
Gas & Battery gauges: check gas & battery levels anytime
Start & Go system: energy saving, "self cut-off" when it is not used for 1mn
Low push down force (4.5 kg)
Automatic energy absorber
Automatic gas dosage (used T° - 15 °C to + 49 °C)
Battery charging time: 105 mn (25 mn = 1000 pins)
Fuel cell: 750 shots (20 °C), battery: up to 3500 shots

Safety Specifications
CE marking
Complete tool pressure necessary to generate the shot
Security with on / off led indicator
Noise level, EN 12549 : LpA, 1s, 1m=96dB(A) / Lp Cpeak=135 dB(C)
Vibration, EN ISO 8662-11: 4.1 m-s ⁻²

Accessories	Consumables
50 pins magazine WARNING: incompatible with Pulsa lift	C6, HC6, CG6, CT-CLIP, E-CLIP, E-CAV, CLIPELEC, ...TRH-CLIP
Magnetic pin guide	Metal P-CLIP, Metal Clip Elec
Cleaning kit	
Pulsa E-Lift Pole Tool	