



READY FOR THE TOUGHEST MISSIONS.

Tested safety for your protection: With our mobile solid rubber distributors you can rely on a trouble-free experience at changing locations. GIFAS stands for proven quality when it comes to materials and components, ensuring that things run smoothly on site.

Small distributors	44
Adapters	45
Industrial distributors	46
Distributor on hinged stand	50
Moveable distributors	51
Inspection trolleys	52
Application cases	53

Small distributors

Series 1400 / 1800 / 2000

Item no.	Symbols Output	Output	Input	Cable/personal protection
----------	----------------	--------	-------	---------------------------

Series 1400 / 78x290x91mm Weight 2-2,5kg Protection category IP54

Assembly variants



Item no. 210521



210502		2 protective contact 230V	3m 3x1.5mm ² Protective contact	RCCB 25/0.03A 2p.
246104		2 protective contact 230V	3m 3x1.5mm ² CEE 3x16A/230V	RCCB 25/0.03A 2p.
210521		4 protective contact 230V	3m 3x1.5mm ² Protective contact	
241761		4 protective contact 230V	5m 3x1.5mm ² Protective contact	

can be supplied with transparent protective cap for max. 2 automated units

Series 1800 / 92x184x53mm Weight 2kg Protection category IP54

Assembly variants



Item no. 101294



101291		3 protective contact 230V	Anti-kink sleeve 3x1.5mm ²	
101294		3 protective contact 230V	3m 3x1.5mm ² Protective contact	
101296		3 protective contact 230V	5m 3x1.5mm ² Protective contact	
101297		3 protective contact 230V	10m 3x1.5mm ² Protective contact	
200804		3 protective contact 230V	3m 5x2.5mm ² CEE 5x16A/400V	

Series 2000 / 130x115x130mm Weight 2-3kg Protection category IP54

Assembly variants



Item no. 101329



101329		3 protective contact 230V	3m 5x2.5mm ² CEE 5x16A/400V	
101337		1 CEE 5x16A/400V 2 protective contact 230V	3m 5x2.5mm ² CEE 5x16A/400 V	
101344		3 CEE 2x16A/24V	3m 2x2.5mm ² CEE 2x16A/24V	
101353		3 CEE 2x16A/42V	3m 2x2.5mm ² CEE 2x16A/42V	
114899		3 CEE 4x16A/>50V, 10h high-frequency 100-300Hz	3m 4x2.5mm ² CEE 4x16A/>50V, 10h high-frequency 100-300Hz	

with 4 adjustable feet and carrying handle


Tailored, customised equipment according to choice.

Series 2516

Item no.	Symbols Output	Output	Input	Cable/personal protection
----------	----------------	--------	-------	---------------------------

Series 2516 / 250x160x90mm Weight ca. 2-4kg Protection category IP54

Assembly variants



209807		4 protective contact 230V	3m 3x1.5mm ² Protective contact	RCCB 25/0.03A 2p.
237370		4 protective contact 230V	5m 3x1.5mm ² Protective contact	PRCD-S 16/0,03A
210397		6 protective contact 230V	3m 5x2.5mm ² CEE 5x16A/400V	
237840		1 CEE 5x16A/400V	3m 5x2.5mm ² CEE 5x16A/400V	RCCB 25/0.03A 4p.
237843		1 CEE 5x32A/400V	3m 5x6mm ² CEE 5x32A/400V	RCCB 40/0.03A 4p.
247671		3 CEE 2x16A/24V	1 KV M20 from below	

Distributors equipped with solid rubber-carrying handle

TOP!



Item no. 209807



Item no. 237370

Adapters

Notes

- The setup requirements for adapters are subject to the conditions of VDE series 0623 - especially part 4 - or in approximation to these.
- An adapter always comprises three parts and is made up of a plug, connecting cable and socket part (e.g. connector socket).
- The flexible connecting cable must be at least 1 m long in order to relieve strain on the wall-mounted socket.
- Not permitted are single-part adapters in which the plug and socket part of both systems are mechanically built together and operated from a single socket since the sockets are not designed for the resulting mechanical rigidity in the event of horizontal and vertical tensile stresses (lever effect).
- Adapters are only intended for short-term use, therefore a clearly visible external warning >For time-limited use only< is required.

Item no.	Output	Input	Cable / personal protection
251882	1 protective contact 230V	2m 5x2.5mm ² CEE plug 5x16A/400V	1 MCB 16A.1PB
251883	1 protective contact 230V	2m 5x6,0mm ² CEE plug 5x32A/400V	1 MCB 16A.1PB
251885	1 CEE 5x16A/400V	2m 5x6,0mm ² CEE plug 5x32A/400V	1 MCB 16A.3PC
251935	1 CEE 5x16A/400V	2m 5x16.0mm ² CEE plug 5x63A/400V	1 MCB 16A.3PC
251886	1 CEE 5x32A/400V	2m 5x16.0mm ² CEE plug 5x63A/400V	1 MCB 32A.3PC

TOP!



Item no. 251883 and 251882



Item no. 251885



Item no. 251935 and 251886

Industrial distributors

Series 3500

Item no.	Symbols Output	Output	Input	Cable/personal protection
----------	----------------	--------	-------	---------------------------

Series 3500 / 361x250x361mm Weight ca. 8-15kg Protection category IP54

Assembly variants



Item no. 278888



Item no. 204884

209284		1 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	3m 5x6mm ² CEE 5x32A/400V	Neozed 16A Neozed 16A
117675		1 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	3m 5x6,0mm ² CEE 5x32A/400V	Neozed 16A Neozed 16A RCCB 40/0.03A 4p.
209285		1 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	3m 5x16.0mm ² CEE 5x63A/400V	Neozed 25A Neozed 16A Neozed 16A
201655		1 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	3m 5x16.0mm ² CEE 5x63A/400V	Neozed 25A Neozed 16A Neozed 16A RCCB 63/0.03A 4p.
204884		1 CEE 5x63A/400V 1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	3m 5x16.0mm ² CEE 5x63A/400V	Neozed 25A Neozed 16A Neozed 16A
112221		1 CEE 5x63A/400V 1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	3m 5x16.0mm ² CEE 5x63A/400V	Neozed 25A Neozed 16A Neozed 16A RCCB 63/0.03A 4p.
209286		2 CEE 5x63A/400V 1 CEE 5x32A/400V 3 protective contact 230V	3m 5x16.0mm ² CEE 5x63A/400V	Neozed 35A Neozed 16A
207770		2 CEE 5x63A/400V 1 CEE 5x32A/400V 3 protective contact 230V	3m 5x16.0mm ² CEE 5x63A/400V	Neozed 35A Neozed 16A RCCB 63/0.03A 4p.
278888		1 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	3m 5x6mm ² CEE 5x63A/400V	1 MCB 32A.3PC 2 MCB 16A.3PC 4 MCB 16A.1PB AC/DC sensitive RCCB 63/0.03A 4p.

- can also be supplied with circuit breaker switch
- with transparent protective cap for max. 11 automated units or 15 automated units can be supplied inside distributor base, with 4 adjustable feet and carrying handle


Tailored, customised equipment according to choice.

Series 3800 PRCD-S inside / 6200

Item no.	Symbols Output	Output	Input	Cable/personal protection
----------	----------------	--------	-------	---------------------------

Series 3800 PRCD-S inside / 250x360x132mm Weight 5-8kg Protection category IP54

Assembly variants




291353		1 CEE 5x16A/400V	3m 5x2,5mm ² CEE 5x16A/400V	PRCD-S 400V/16A
291351		1 CEE 5x32A/400V	3m 5x6mm ² CEE 5x32A/400V	PRCD-S 400V/32A



Illustration similar

Series 6200 / 280x275x230mm Weight ca. 6-8kg Protection category IP54

Assembly variants



208405		6 protective contact 230V	CEE 5x16A/400V device connector	RCCB 25/0.03A 4p.
208981		1 CEE 5x16A/400V 3 protective contact 230V	3m 5x2.5mm ² CEE 5x16A/400V	RCCB 25/0.03A 4p.
207754		1 CEE 5x16A/400V 3 protective contact 230V	3m 5x2.5mm ² CEE 5x16A/400V	
209315		1 CEE 5x16A/400V 3 protective contact 230V	CEE 5x16A/400V connector plug	
208979		1 CEE 5x16A/400V 3 protective contact 230V	3m 5x6,0mm ² CEE 5x32A/400V	Neozed 16A Neozed 16A
207755		1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	3m 5x6,0mm ² CEE 5x32A/400V	Neozed 16A Neozed 16A

- can also be supplied with circuit breaker switch
- with max. 9 automated units inside located under the cover plate

TOP !



Item no. 207755

TOP !



Automated units under cover plate

Tailored, customised equipment according to choice.


Industrial distributors

Series 6700 / 7900

Item no.	Symbols Output	Output	Input	Cable/personal protection
----------	----------------	--------	-------	---------------------------

Series 6700 / 350x305x280mm Weight ca. 12-14kg Protection category IP54

Assembly variants



TOP !

TOP !



Item no. 209311



Item no. 240184 with Marechal-sockets

209311		1 CEE 5x32A/400V 1 CEE 5x16A/400V 2 protective contact 230V	3m 5x6,0mm ² CEE 5x32A/400V	MCB 16A.3PC MCB 16A.1PB RCCB 40/0.03A 4p.
208959		1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	3m 5x6,0mm ² CEE 5x32A/400V	Neozed 16A Neozed 16A RCCB 40/0.03A 4p.
209307		1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	3m 5x16,0mm ² CEE 5x63A/400V	MCB 32A.3PC MCB 16A.3PC MCB 16A.1PB
208960		1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	3m 5x16,0mm ² CEE 5x63A/400V	Neozed 25A Neozed 16A Neozed 16A RCCB 63/0.03A 4p.
209516		1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	CEE 5x63A/400V device connector	Neozed 25A Neozed 16A Neozed 16A RCCB 63/0.03A 4p.
209167		1 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	3m 5x6,0mm ² mit CEE 5x32A/400V	Neozed 16A Neozed 16A
209515		1 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	CEE 5x32A/400V device connector	Neozed 16A Neozed 16A
209517		1 CEE 5x63A/400V 1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	CEE 5x63A/400V device connector	MCB 32A.3PC MCB 16A.3PC MCB 16A.1PB RCCB 63/0.03A 4p.
240184		1 Marechal-sockets 5x90-150A/500V	1 bellmouth cable gland M 50	RCCB 125/0.03A 4p.

Series 7900 / 360x500x173mm Weight 23kg Protection category IP54

with main switch

Assembly variants



Item no. 231829

231829		12 protective contact 230V	3m 5x6,0mm ² CEE 5x32A/400V	MCB 16A.1PC RCCB 40/0.03A 4p. for 6 protective contact each
--------	--	----------------------------	---	--


Tailored, customised equipment according to choice.

Series 7900

Item no.	Symbols Output	Output	Input	Cable/personal protection
----------	----------------	--------	-------	---------------------------

Series 7900 / 360x500x173mm Weight 23kg Protection category IP54

Assembly variants



209257		2 CEE 5x16A/400V 6 protective contact 230V	CEE 5x32A/400V device connector	Neozed 16A MCB 16A.1PB RCCB 40/0.03A 4p. RCCB 40/0.03A 4p.
210631		1 CEE 5x32A/400V 2 CEE 5x16A/400V 9 protective contact sockets 230V	3m 5x6.0mm ² CEE 5x32A/400V	Neozed 25A Neozed 16A Neozed 16A RCCB 40/0.03A 4p. f.6 protective contacts RCCB 40/0.03A 4p. f. remaining sockets
230776		1 CEE 5x32A/400V 4 CEE 5x16A/400V 3 protective contact sockets 230V	3m 5x16.0mm ² CEE 5x63A/400V	Neozed 25A Neozed 16A Neozed 16A RCCB 63/0.03A 4p. for CEE RCCB 25/0.03A 4p. for protective contact
210884		2 CEE 5x32A/400V 6 protective contact 230V	3m 5x16.0mm ² CEE 5x63A/400V	Neozed 25A MCB 16A.1PB RCCB 63/0.03A 4p. RCCB 40/0.03A 4p.
233393		2 CEE 5x32A/400V 4 CEE 5x16A/400V 3 protective contact sockets 230V	3m 5x16.0mm ² CEE 5x63A/400V	MCB 32A.3PC MCB 16A.3PC MCB 16A.1PB RCCB 63/0.03A 4p. for CEE 32A and protective contact RCCB 63/0.03A 4p. for CEE 16A
210630		1 CEE 5x32A/400 V 2 CEE 5x16A/400 V 10 protective contact 230V	3m 5x6.0mm ² CEE 5x32A/400V	Neozed 25A Neozed 16A Neozed 16A RCCB 40/0.03A 4p.
204298		1 CEE 5x63A/400V 2 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	3m 5x16.0mm ² CEE 5x63A/400V	Neozed 63A Neozed 25A Neozed 16A Neozed 16A RCCB 63/0.03A 4p.
211029		2 CEE 5x63A/400V 2 CEE 5x32A/400V 3 protective contact 230V	CEE 5x125A/400V device connector	Neozed 63A Neozed 25A Neozed 16A RCCB 125/0.03A 4p.
277359		12 protective contact sockets 230V	CEE 5x32A/400V device connector	12 MCB 16A.1PC 12 RCCB 40/0.03A 4p. for 6 protective contact

- with max. 51 automated units (17 per transparent protective cap), with 4 adjustable feet and 1 or 2 carrying handles
- Distributor equipped with transport handle and leveling feet

TOP !



7900 engraving according to customers requirements



7900 buildin in a protective aluminum frame

Tailored, customised equipment according to choice.

NEW

Distributor on hinged stand



7300 on hinged stand



7400 on hinged stand



7700 on hinged stand

For complex applications (e.g. larger temporary construction sites) wall-mounted distribution boxes with handles are available as an alternative to the classic design of mobile distribution boxes. These can be mounted on a hinged frame. Flexible, versatile assembly options allow the appropriate power supply on site. Thanks to the universal hinged frame, series 7200 to 7700 distribution boxes can be used.

Product features hinged stand

- Mobile solution for larger distributors with a wide range of equipment options
- Practical carry case
- Mounting holes for different series
- Solid stainless steel version in V2A
- Protective devices can be viewed and operated directly via the transparent protection flap
- Better operability due to elevated position
- Protection against waterlogging

Technical data

Material V2A stainless steel I
Dimensions (HxWxD) 569x400x40mm

Item no.	Description
294668	Hinged stand for distributors of the series 7200 - 7700



Optional:
Stand MINI with double feet

Moveable distributors

Item no.	Symbols Output	Output	Input	Cable/personal protection
Distributor 7900 / 360x500x173mm Protection category IP54 Zinc-plated chassis / 450x977x447mm Weight ca. 55kg				
209455		1 CEE 5x63A/400V 1 CEE 5x32A/400V 2 CEE 5x16A/400V 6 protective contact sockets 230V	3m 5x16mm ² CEE 5x63A/400V	Neozed 32A Neozed 16A 6 MCB 16A.1PB RCCB 63/0.03A 4p. for all CEE RCCB 40/0.03A 4p. for all protective contacts, IP54
279096		1 CEE 5x63A/400V 1 CEE 5x32A/400V 2 CEE 5x16A/400V 6 protective contact sockets 230V	3m 5x16mm ² CEE 5x63A/400V	Neozed 32A Neozed 16A 6 MCB 16A.1PB RCCB 63/0.03A 4p. for all CEE RCCB 40/0.03A 4p. for all protective contacts, IP67



Item no. 209455

Item no. 279096

Distributor 7400 / 265x370x132mm Protection category IP54
Hand truck / 566x1200x560mm Weight ca. 81kg

233431		1 CEE 5x32A/400V 1 CEE 5x16A/400V 2 protective contact 230V	40m 5x6mm ² CEE 5x32A/400V	1 MCB 16A.3PC 2 MCB 16A.1PB RCCB 40/0.03A 4p.
--------	--	---	--	---



Item no. 233431

Item no. 295316

Distributor 6700 / 305x350x280mm Protection category IP54
Barrow / 566x1200x560mm Weight ca. 65kg

295316		1 CEE 5x32A/400V 1 CEE 5x16A/400V 2 protective contact 230V	2m 5x6mm ² CEE 5x32A/400V 1 energy meter 1 Kunbus Revolution Pi 1 control fuse 2A 1 power supply unit 24 V 1 glass tube fuse 1A 1 RJ45 data socket	1 MCP 16A.3PC 2 MCP 16A.1PB RCCB 40/0.03A 4p.
--------	--	---	--	---

Distributor 7800 / 360x500x133mm Protection category IP54
Sheet steel cable reel red 521 movable / 720x1130x775mm Weight ca. 90kg

207356		2 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	25m 5x16mm ² CEE 5x63A/400V	Neozed 32A Neozed 16A 3 MCB 16A.1PB RCCB 25/0.03A 4p.
--------	--	---	---	--



Item no. 207356

Tailored, customised equipment according to choice.

Inspection trolley / Mobil electronic frequency converter / Test unit

These products are equipped entirely in accordance with your wishes and requirements. Our experience and your needs are perfectly tuned to produce the ideal solution. The possibilities are virtually limitless.

Possible areas of use

aircraft construction, automotive industry, tool manufacturing, major inspections, assembly, large-scale construction sites, testing and assembly stations in industry, concerts and festivals, theatre stages

Installation possibilities

transformers (three-phase current, safety or isolating transformers), control elements, measuring equipment, fuse elements, control lights, insulation monitors, plug connectors, and much more



Test unit



Inspection trolley



Inspection trolley



Mobile frequency converter



Inspection trolley „3 in 1“ - transformer, big cable reel, trailer, rotary current transformer


Tailored, customised equipment according to choice.

Application cases mobile distributor



WE ARE EXPERTS IN YOUR FIELD


Mobile distributors



Construction industry



Industrial sector



Safety equipment

The GIFAS World.

All products for your sector at a glance.

More on www.gifas.de/en/gifas-world