

Earth Rod to Cable 'G' Clamps

These clamps are used for joining earth rods to different sizes of stranded copper conductor. The clamps have a high resistance to corrosion and are mechanically strong to ensure a lasting connection.

Earth Rod Shank Ø mm	Conductor Range mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
9.5	6 - 35	30	20	15	0.05	25	ERR 1035
12.7	6 - 35	36	28	18	0.07	25	ERR 1635
	35 - 70	41	26	20	0.08	50	ERR 1670*
14.2	6 - 16	36	28	18	0.07	25	ERR 1635
	16 - 70	41	26	20	0.08	50	ERR 1670*
	35 - 150	48	30	18	0.09	50	ERR 2095*
15.0	6 - 16	36	28	18	0.07	25	ERR 1635
	16 - 70	41	26	20	0.08	50	ERR 1670*
	25 - 150	48	30	18	0.09	50	ERR 2095*
16.0	6 - 70	41	26	20	0.08	50	ERR 1670*
	16 - 150	48	30	18	0.09	50	ERR 2095*
17.2	6 - 95	48	30	18	0.09	50	ERR 2095*
20.0	16 - 95	48	30	18	0.09	50	ERR 2095*

Material: High Copper Alloy with M10 x 25mm Phosphor Bronze Set Screw

* Suitable for use with 8mm Ø solid circular copper conductor.



BS EN 62561-1 Class H



Tightening Torque 12 Nm; ERR1635 13 Nm; ERR2095 20 Nm

ERR 1035



ERR 1635



ERR 1670



ERR 2095

