



## Metallic DC Clips

Metallic DC clips secure the flat tape conductor to the building surface. Fix using countersunk woodscrews 1 1/2" x No. 10 and No. 10 wall plug.

### For use with Bare Copper Tapes

Conductor Size mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
20 x 3	50	21	10	0.06	50	DCG 203
25 x 3	51		10	0.05	50	DCB 253
25 x 4	51		11	0.05	50	DCG 254
25 x 6	51		12	0.05	50	DCG 256
30 x 2	56		9	0.05	25	DCG 302
30 x 5	56		12	0.06	25	DCG 305
31 x 3	60		10	0.07	25	DCG 313
31 x 4	56		11	0.07	25	DCG 314
31.5 x 4	56		11	0.06	25	DCG 3154
31 x 6	56		12	0.06	25	DCG 316
38 x 3	69		10	0.06	25	DCG 383
38 x 5	64		12	0.09	25	DCG 385
38 x 6	69		12	0.08	25	DCG 386
40 x 3	70		10	0.07	50	DCG 403
40 x 4	69		11	0.07	25	DCG 404
40 x 5	69		12	0.07	50	DCG 405
40 x 6	69		12	0.08	25	DCG 406
50 x 3	76		10	0.06	25	DCG 503
50 x 4	76		11	0.09	50	DCG 504
50 x 6	76		12	0.06	25	DCB 506
50 x 8	76	14	0.08	25	DCG 508	
60 x 5	90	11	0.10	25	DCG 605	
63 x 10	102	25	16	0.13	25	DCG 6310
70 x 5	110		13	0.14	25	DCG 705
75 x 6	110		14	0.14	25	DCG 756
80 x 5	110		11	0.14	25	DCG 805
80 x 6	110		14	0.14	25	DCG 806

Material: High Copper Alloy.

### For use with PVC Covered Copper Tapes

Conductor Size mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
25 x 3	56	21	12	0.06	50	DGP 253
25 x 6	56		15	0.07	25	DGP 256
50 x 6	90	25	16	0.13	25	DGP 506

Material: High Copper Alloy.

### For use with Lead Covered Copper Tape

Conductor Size mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
31 x 7	60	20	14	0.08	25	DCG 317



Material: High Copper Alloy.



BS EN 62561-4



Tightening torque 6 Nm



## Metallic DC Clips (continued)

For use with Bare Aluminium Tapes

Conductor Size mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
25 x 3	52	21	10	0.02	50	DCA 253
25 x 6	50		13	0.03		DCA 256
50 x 6	76		12	0.03	25	DCA 506
60 x 6	90		17	0.05		DCA 606



DCA 253

Material: Aluminium.

For use with PVC Covered Aluminium Tapes

Conductor Size mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
25 x 3	55	20	20	0.03	25	DAP 253
50 x 6	85		23	0.04		DAP 506

Material: Aluminium.



BS EN 62561-4



Tightening torque 6 Nm