

# TAPCON CSK



## PRODUCT DESCRIPTION

- Self tapping screw with countersunk head for fastening into cracked & non-cracked concrete

## PRODUCT PROMISE

ETA Approved, fire rated, industry leading high performance concrete anchor

## FEATURES AND BENEFITS

- Complete range ETA Option 1 can be used in cracked & non-cracked concrete
- Fire approval
- C1 seismic approval for Ø6
- Longer effective thread allows highest performance within the market
- New patented thread design provides easy setting
- Adjustable anchor for alignment situations when required without loss of performance
- Large choice of drilling diameters & lengths
- 3 anchoring depths for Ø6 & Ø8

## APPROVALS



## APPLICATIONS

- Trunking
- Hanging Services From Ceiling or From Walls
- Suspended Ceiling
- Temporary fixings
- Scaffolding
- Road Signs
- Safety Barriers
- Stadium Seating
- Pallet Racking
- M&E
- Cable trays
- Window Frames
- Railings
- HVAC

## SUBSTRATES



## PRODUCT RANGE

Anchor Length ▲▼	Quantity ▲▼	Product Code ▲▼	Diameter Anchor ▲▼	Min. Drilling Depth ▲▼	Max. Embedment Depth ▲▼
40 mm	100	058770	5 -	40 mm	35 mm
40 mm	100	058772	6 -	40 mm	35 mm
60 mm	100	058771	5 -	40 mm	35 mm
60 mm	100	058773	6 -	40 mm	55 mm
80 mm	100	058774	6 -	40 mm	55 mm
100 mm	100	058775	6 -	40 mm	55 mm
120 mm	100	058776	6 -	40 mm	55 mm
140 mm	100	058777	6 -	40 mm	55 mm