

TAPCON HFL



PRODUCT DESCRIPTION

- Self tapping screw with hexagonal head for fastening into cracked & non-cracked concrete

PRODUCT PROMISE

ETA Approved, fire rated, industry leading high performance concrete anchor

FEATURES AND BENEFITS

- Complete range ETA Option 1 can be used in cracked & non-cracked concrete
- Fire approval
- C1 seismic approval for Ø6
- Longer effective thread allows highest performance within the market
- New patented thread design provides easy setting
- Adjustable anchor for alignment situations when required without loss of performance
- Large choice of drilling diameters & lengths
- 3 anchoring depths for Ø6

APPROVALS



APPLICATIONS

- Formwork
- Mechanical and electrical
- Façade and curtain walls
- Demolition
- Safety barriers and hand rails
- Security gates and fencing
- Racking and storage
- Machinery and equipment
- Stadium seating
- Signage and lighting
- Infrastructure - energy, road, rail
- HVAC

SUBSTRATES



PRODUCT RANGE

Anchor Length ▲▼	Quantity ▲▼	Product Code ▲▼	Diameter Anchor ▲▼	Min. Drilling Depth ▲▼	Max. Embedment Depth ▲▼
40 mm	100	058726	5 -	40 mm	35 mm
40 mm	100	058729	6 -	40 mm	35 mm
50 mm	100	058727	5 -	40 mm	35 mm
50 mm	100	058730	6 -	40 mm	35 mm
60 mm	100	058728	5 -	40 mm	35 mm
80 mm	100	058731	6 -	40 mm	55 mm
100 mm	100	058732	6 -	40 mm	55 mm