

TAPCON HFL XTREM



PRODUCT DESCRIPTION

- Self tapping screw with hexagonal head for fastening into cracked & non-cracked concrete & for seismic applications

PRODUCT PROMISE

ETA Seismic Approved, fire rated, industry leading high performance concrete anchor

FEATURES AND BENEFITS

- Complete range ETA Option 1 can be used in cracked & non-cracked concrete
- TAPCON XTREM range approved for C1 and C2 seismic applications
- Fire approval
- Longer effective thread allows highest performance within the market
- New patented thread design provides easy setting
- Adjustable anchor for re-alignment without loss of performance
- Removable anchor allows for temporary fixings
- Large choice of drilling diameters, heads & lengths

APPROVALS



APPLICATIONS

- Formwork
- Mechanical and electrical
- Façade and curtain walls
- Demolition
- Safety barriers and hand rails
- Security gates and fencing
- Racking and storage
- Machinery and equipment
- Stadium seating
- Signage and lighting
- Infrastructure - energy, road, rail
- HVAC

SUBSTRATES



PRODUCT RANGE

Anchor Length ▲▼	Quantity ▲▼	Product Code ▲▼	Diameter Anchor ▲▼	Min. Drilling Depth ▲▼	Max. Embedment Depth ▲▼
50 mm	50	058733	8 -	55 mm	-
60 mm	50	058734	8 -	55 mm	-
60 mm	50	058740	10 -	65 mm	-
70 mm	50	058735	8 -	55 mm	65 mm
70 mm	50	058741	10 -	65 mm	-
80 mm	25	058747	12 -	75 mm	-
80 mm	50	058736	8 -	55 mm	65 mm
90 mm	50	058742	10 -	65 mm	55 mm
100 mm	50	058737	8 -	55 mm	65 mm
100 mm	50	058743	10 -	65 mm	85 mm
110 mm	25	058748	12 -	75 mm	100 mm
120 mm	50	058738	8 -	55 mm	65 mm
120 mm	50	058744	10 -	65 mm	85 mm
130 mm	25	058768	14 -	85 mm	115 mm
140 mm	50	058739	8 -	55 mm	65 mm
140 mm	50	058745	10 -	65 mm	85 mm
150 mm	25	058769	14 -	85 mm	115 mm
160 mm	50	058746	10 -	65 mm	85 mm