



KRASO® Sealing Insert Type SD
Here there is an installation video
(just scan in the QR-Code!)

**Generally ready for
dispatch within 24 hours!**



KRASO® Sealing Insert Type SD A type for special situations

- + Torque Control Nut **KRASO® DKM**: integrated torque limiter - no torque wrench required!
- + Whenever it gets complicated: this is the individual and custom-made solution for your sealing problem!
With large flange, eccentric or split...
- + 30 or 60 mm seal: proof against pressing water up to 2,5 or 5 bar (MPA-tested)!
High-quality in terms of TA-Air! Radon-tight!
- + **KRASO® Sealing Insert quality**: 5 mm thick clamping plates made of non-corrosive stainless steel V2A,
30 mm/60 mm seal made of specially developed rubber mixture, welded-on studs instead of through bolts.
- + With arrangement template: see at a glance the arrangement of media lines, pipes and cables!
- + Generally ready for dispatch within 24 hours!
- + Available for an additional charge:
 - non-corrosive stainless steel V4A
 - KTW - recommendation
 - NBR - oil- and petrol resistant
 - Temperature resistant up to 220 °C.



KRASO® Type SD 30



KRASO® Type SD 30 - T



KRASO® Type SD 30 - E



KRASO® Type SD 30 - GF

KRASO® Sealing Insert Type SD 30 • KRASO® Sealing Insert Type SD 60

LG 1

for installation of pipes or cables, Torque Control Nut **KRASO® DKM***

KRASO® Type SD 30 - T, split / **KRASO® Type SD 30 - E**, eccentric / **KRASO® Type SD 30 - GF**, large flange

KRASO® Type SD 60 - T, split / **KRASO® Type SD 60 - E**, eccentric / **KRASO® Type SD 60 - GF**, large flange