

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

Standard: UL 224



• Shrink Ratio:	2:1.
• Material:	Polyolefin - Standard wall heat shrink tube.
• Operating Temperature:	-55°C to +125°C.
• Shrink Properties:	Shrinkable temperature: 80°C.
• Features:	Flame retardant, very good chemical and solvent resistance, excellent electrical and physical properties, flexible and high dielectric strength. Chemical resistance: Fuel, hydraulic fluid and lubricating oil.
• Application:	Electrical insulation, cable bundling, pipes and wires giving good physical protection.



PLEASE NOTE: Red Heat Shrink Tubing is NOT Halogen Free

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
H1.2-BLA	Black	300	1.2	0.6	0.36 (±0.10)
H1.6-BLA	Black	300	1.6	0.8	0.36 (±0.10)
H2.4-BLA	Black	150	2.4	1.2	0.45 (±0.10)
H3.2-BLA	Black	150	3.2	1.6	0.45 (±0.10)
H4.8-BLA	Black	60	4.8	2.4	0.56 (±0.10)
H6.4-BLA	Black	60	6.4	3.2	0.56 (±0.10)
H9.5-BLA	Black	60	9.5	4.8	0.56 (±0.10)
H12.7-BLA	Black	60	12.7	6.4	0.56 (±0.10)
H19.1-BLA	Black	60	19.1	9.5	0.70 (±0.10)
H25.4-BLA	Black	30	25.4	12.7	0.90 (±0.15)
H38.1-BLA	Black	30	38.1	19.1	1.00 (±0.15)
H50.8-BLA	Black	25	50.8	25.4	1.10 (±0.20)
H76.2-BLA	Black	25	76.2	38.1	1.46 (±0.20)
H101.6-BLA	Black	25	101.6	50.8	1.46 (±0.20)

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
H2.4-BLU	Blue	150	2.4	1.2	0.45 (±0.10)
H3.2-BLU	Blue	200	3.2	1.6	0.45 (±0.10)
H4.8-BLU	Blue	100	4.8	2.4	0.56 (±0.10)
H6.4-BLU	Blue	100	6.4	3.2	0.56 (±0.10)
H9.5-BLU	Blue	100	9.5	4.8	0.56 (±0.10)
H12.7-BLU	Blue	100	12.7	6.4	0.56 (±0.10)
H19.1-BLU	Blue	60	19.1	9.5	0.70 (±0.10)
H25.4-BLU	Blue	30	25.4	12.7	0.90 (±0.15)
H38.1-BLU	Blue	30	38.1	19.1	1.00 (±0.15)
H50.8-BLU	Blue	25	50.8	25.4	1.10 (±0.20)
H76.2-BLU	Blue	25	76.2	38.1	1.46 (±0.20)
H101.6-BLU	Blue	25	101.6	50.8	1.46 (±0.20)
H4.8-BROWN	Brown	100	4.8	2.4	0.56 (±0.10)
H6.4-BROWN	Brown	100	6.4	3.2	0.56 (±0.10)
H9.5-BROWN	Brown	100	9.5	4.8	0.56 (±0.10)
H12.7-BROWN	Brown	60	12.7	6.4	0.56 (±0.10)
H19.1-BROWN	Brown	60	19.1	9.5	0.70 (±0.10)
H25.4-BROWN	Brown	30	25.4	12.7	0.90 (±0.15)
H38.1-BROWN	Brown	30	38.1	19.1	1.00 (±0.15)
H50.8-BROWN	Brown	25	50.8	25.4	1.10 (±0.20)
H76.2-BROWN	Brown	25	76.2	38.1	1.46 (±0.20)
H101.6-BROWN	Brown	25	101.6	50.8	1.46 (±0.20)
H1.2-CLR	Clear	300	1.2	0.6	0.36 (±0.10)
H1.6-CLR	Clear	300	1.6	0.8	0.36 (±0.10)
H2.4-CLR	Clear	150	2.4	1.2	0.45 (±0.10)
H3.2-CLR	Clear	150	3.2	1.6	0.45 (±0.10)
H4.8-CLR	Clear	75	4.8	2.4	0.56 (±0.10)
H6.4-CLR	Clear	60	6.4	3.2	0.56 (±0.10)
H9.5-CLR	Clear	60	9.5	4.8	0.56 (±0.10)
H12.7-CLR	Clear	60	12.7	6.4	0.56 (±0.10)
H19.1-CLR	Clear	60	19.1	9.5	0.70 (±0.10)
H25.4-CLR	Clear	30	25.4	12.7	0.90 (±0.15)
H2.4-GRN	Green	150	2.4	1.2	0.45 (±0.10)
H3.2-GRN	Green	200	3.2	1.6	0.45 (±0.10)
H4.8-GRN	Green	100	4.8	2.4	0.56 (±0.10)
H6.4-GRN	Green	100	6.4	3.2	0.56 (±0.10)

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
H9.5-GRN	Green	100	9.5	4.8	0.56 (±0.10)
H12.7-GRN	Green	100	12.7	6.4	0.56 (±0.10)
H19.1-GRN	Green	60	19.1	9.5	0.70 (±0.10)
H25.4-GRN	Green	30	25.4	12.7	0.90 (±0.15)
H3.2-G/Y	Green Yellow	200	3.2	1.6	0.45 (±0.10)
H4.8-G/Y	Green Yellow	100	4.8	2.4	0.56 (±0.10)
H6.4-G/Y	Green Yellow	100	6.4	3.2	0.56 (±0.10)
H9.5-G/Y	Green Yellow	100	9.5	4.8	0.56 (±0.10)
H12.7-G/Y	Green Yellow	100	12.7	6.4	0.56 (±0.10)
H19.1-G/Y	Green Yellow	60	19.1	9.5	0.70 (±0.10)
H25.4-G/Y	Green Yellow	30	25.4	12.7	0.90 (±0.15)
H38.1-G/Y	Green Yellow	30	38.1	19.1	1.00 (±0.15)
H50.8-G/Y	Green Yellow	25	50.8	25.4	1.10 (±0.20)
H76.2-G/Y	Green Yellow	25	76.2	38.1	1.46 (±0.20)
H101.6-G/Y	Green Yellow	25	101.6	50.8	1.46 (±0.20)
H4.8-GREY	Grey	100	4.8	2.4	0.56 (±0.10)
H6.4-GREY	Grey	100	6.4	3.2	0.56 (±0.10)
H9.5-GREY	Grey	100	9.5	4.8	0.56 (±0.10)
H12.7-GREY	Grey	60	12.7	6.4	0.56 (±0.10)
H19.1-GREY	Grey	60	19.1	9.5	0.70 (±0.10)
H25.4-GREY	Grey	30	25.4	12.7	0.90 (±0.15)
H38.1-GREY	Grey	30	38.1	19.1	1.00 (±0.15)
H50.8-GREY	Grey	25	50.8	25.4	1.10 (±0.20)
H76.2-GREY	Grey	25	76.2	38.1	1.46 (±0.20)
H101.6-GREY	Grey	25	101.6	50.8	1.46 (±0.20)
H2.4-RED	Red	150	2.4	1.2	0.45 (±0.10)
H3.2-RED	Red	200	3.2	1.6	0.45 (±0.10)
H4.8-RED	Red	100	4.8	2.4	0.56 (±0.10)
H6.4-RED	Red	100	6.4	3.2	0.56 (±0.10)
H9.5-RED	Red	100	9.5	4.8	0.56 (±0.10)
H12.7-RED	Red	100	12.7	6.4	0.56 (±0.10)
H19.1-RED	Red	60	19.1	9.5	0.70 (±0.10)
H25.4-RED	Red	30	25.4	12.7	0.90 (±0.15)
H38.1-RED	Red	30	38.1	19.1	1.00 (±0.15)
H50.8-RED	Red	25	50.8	25.4	1.10 (±0.20)
H76.2-RED	Red	25	76.2	38.1	1.46 (±0.20)

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
H2.4-WHT	White	150	2.4	1.2	0.45 (±0.10)
H3.2-WHT	White	150	3.2	1.6	0.45 (±0.10)
H4.8-WHT	White	75	4.8	2.4	0.56 (±0.10)
H6.4-WHT	White	60	6.4	3.2	0.56 (±0.10)
H9.5-WHT	White	60	9.5	4.8	0.56 (±0.10)
H12.7-WHT	White	60	12.7	6.4	0.56 (±0.10)
H19.1-WHT	White	60	19.1	9.5	0.70 (±0.10)
H25.4-WHT	White	30	25.4	12.7	0.90 (±0.15)
H38.1-WHT	White	30	38.1	19.1	1.00 (±0.15)
H50.8-WHT	White	25	50.8	25.4	1.10 (±0.20)
H76.2-WHT	White	25	76.2	38.1	1.46 (±0.20)
H2.4-YLW	Yellow	150	2.4	1.2	0.45 (±0.10)
H3.2-YLW	Yellow	200	3.2	1.6	0.45 (±0.10)
H4.8-YLW	Yellow	100	4.8	2.4	0.56 (±0.10)
H6.4-YLW	Yellow	100	6.4	3.2	0.56 (±0.10)
H9.5-YLW	Yellow	100	9.5	4.8	0.56 (±0.10)
H12.7-YLW	Yellow	100	12.7	6.4	0.56 (±0.10)
H19.1-YLW	Yellow	60	19.1	9.5	0.70 (±0.10)
H25.4-YLW	Yellow	30	25.4	12.7	0.90 (±0.15)
H38.1-YLW	Yellow	30	38.1	19.1	1.00 (±0.15)
H50.8-YLW	Yellow	25	50.8	25.4	1.10 (±0.20)
H76.2-YLW	Yellow	25	76.2	38.1	1.46 (±0.20)