#### PRODUCT CARD

2/13/2024

# **ENSTO**

## Cold shrink indoor term

CIT1.2404L

Code CIT1.2404L

GTIN 6438100302856

Name Cold shrink indoor term

12.7/22 (24) kV 185-300 mm<sup>2</sup> 3x1-core with

lug

Description Cold shrink indoor termination for 1-core

cables with Al/Cu conductor, polymeric insulation and Cu-wire screen. The kit contains components for three cable cores. Mechanical lugs for conductor and screen wire connection are included in the kit. The termination kits include cold

shrinkable termination bodies with integrated geometric stress control elements and all the additional components needed for assembly.

Vendor Ensto Finland Oy



# Technical specification

### **Features**

Rated voltage U0/U (Um): 12.7/22 (24) kV
Shrink technique: Cold shrink

Accessory type: Termination, indoor

**Conductor material:** Al/Cu

Conductor size round:185 ... 300 mm²Screen/shield connection:6 ... 50 mm²Creepage distance:410 mmShed diameter:68 mmInstalled length (L):370 mm

Cable

Conductor size Um = 12 kV:  $240 \dots 300 \text{ mm}^2$ Conductor size Um = 24 kV:  $185 \dots 300 \text{ mm}^2$ Diameter on the insulation:  $25.3 \dots 50 \text{ mm}$ 



Diameter outer sheath:35 ... 53 mmMaterial insulation:PolymericMaterial screen/shield:Cu-wireNumber of cores:3

**Temperatures** 

Installation temperature:  $-25 ... 50 \, ^{\circ}\text{C}$ Operating temperature:  $-50 ... 90 \, ^{\circ}\text{C}$ Storage temperature:  $5 ... 40 \, ^{\circ}\text{C}$ 

Others

ETIM Class: EC003520

**Dimensions** 

Weight: 2.54 kg

# ETIM Technical specification

## etim

Number of cores:3Suitable for indoor use:YesSuitable for outdoor use:No

Type of cable termination: Cold-shrink

Material insulating material: Plastic

Cable lug included: Yes

Type of cable lug: Screw connection

Nominal cross section: 185 ... 300 mm<sup>2</sup>

# Packaging

## Carton (Default package)

 Package size:
 1 pce

 Depth:
 383 mm

 Width:
 258 mm

 Height:
 173 mm

 Weight:
 2.782 kg

 Volume:
 17.094822 l

# Pallet package

 Package size:
 54 pcs

 Depth:
 1200 mm

 Width:
 800 mm

 Height:
 1020 mm

 Weight:
 170.228 kg

 Volume:
 979.2 l

