### PRODUCT CARD

2/13/2024

# **ENSTO**

### Cold shrink indoor term

CIT1.24055L

Code CIT1.24055L

GTIN 6438389104783

Name Cold shrink indoor term

12.7/22 (24) kV 630-800 mm<sup>2</sup> 3x1-core with

lug

Description Cold shrink indoor termination for 1-core

cables with Al/Cu conductor, polymeric insulation and Cu-wire screen. The kit contains components for three cable cores. Mechanical lugs for conductor and screen wire connection are included in the

kit. The termination kits include cold shrinkable termination bodies with integrated geometric stress control elements and all the additional components needed for assembly.

Vendor Ensto Finland Oy



# Technical specification

## **Features**

Rated voltage U0/U (Um): 12.7/22 (24) kV
Shrink technique: Cold shrink

Accessory type: Termination, indoor

Conductor material: Al/Cu

Conductor size round:630 ... 800 mm²Screen/shield connection:6 ... 50 mm²Creepage distance:440 mmShed diameter:78 mmInstalled length (L):420 mm

Cable

Conductor size Um = 12 kV: 800 mm<sup>2</sup>

Conductor size Um = 24 kV: 630 ... 800 mm<sup>2</sup>

Diameter on the insulation: 36.8 ... 72 mm



Diameter outer sheath:47 ... 72 mmMaterial insulation:PolymericMaterial screen/shield:Cu-wireNumber of cores:3

**Temperatures** 

Installation temperature:  $-25 ... 50 \, ^{\circ}\text{C}$ Operating temperature:  $-50 ... 90 \, ^{\circ}\text{C}$ Storage temperature:  $5 ... 40 \, ^{\circ}\text{C}$ 

Others

ETIM Class: EC003520

**Dimensions** 

Weight: 3.4 kg

# ETIM Technical specification

## etim

Number of cores:3Suitable for indoor use:YesSuitable for outdoor use:No

Type of cable termination: Cold-shrink

Material insulating material: Plastic

Cable lug included: Yes

Type of cable lug: Screw connection

Nominal cross section: 630 ... 800 mm<sup>2</sup>

# Packaging

## Carton (Default package)

 Package size:
 1 pce

 Depth:
 508 mm

 Width:
 263 mm

 Height:
 216 mm

 Weight:
 3.716 kg

 Volume:
 28.858464 l

# Pallet package

 Package size:
 24 pcs

 Depth:
 1200 mm

 Width:
 800 mm

 Height:
 1030 mm

 Weight:
 109.184 kg

 Volume:
 988.8 l