ENSTO

PRODUCT SPECIFICATION



Cold shrink joint

CJ11.2403C

Code CJ11.2403C

GTIN 6438100300548 Name Cold shrink joint

12.7/22 (24) kV 70-240mm² 1-core with

connectors

Description Cold shrink joint for 1-core cables with

Al/Cu conductor, polymeric insulation and

Cu-wire screen. The kit contains components for one cable core.

Mechanical connectors are included in the kit. The joint kits include cold shrinkable joint bodies with integrated geometric stress control elements, tubular copper braids for screen connection, cold

shrinkable outer jacket tubes and all the

additional components needed for

assembly.

Vendor Ensto Finland Oy

Technical specification

Features

Rated voltage U0/U (Um): 12.7/22 (24) kV
Shrink technique: Cold shrink

Accessory type: Straight through joint

Conductor material: Al/Cu

Conductor size round: $70 \dots 240 \text{ mm}^2$ Screen/shield connection: $\leq 25 \text{ mm}^2$ Installed length (L): 630 mm

Cable

Conductor size Um = 12 kV: $95 \dots 240 \text{ mm}^2$ Conductor size Um = 24 kV: $70 \dots 240 \text{ mm}^2$ Diameter on the insulation: $18.4 \dots 36 \text{ mm}$ Diameter outer sheath: $27.5 \dots 42 \text{ mm}$



Material insulation:PolymericMaterial screen/shield:Cu-wire

Number of cores: 1

Temperatures

Installation temperature: $-25 ... 50 \, ^{\circ}\text{C}$ Operating temperature: $-50 ... 90 \, ^{\circ}\text{C}$ Storage temperature: $5 ... 40 \, ^{\circ}\text{C}$

Others

ETIM Class: EC001169

Dimensions

Weight: 2.28 kg

ETIM Technical specification

etim

Rated voltage U0/U (Um):12.7/22 (24) kVModel:Cold-shrinkMaterial insulating material:Plastic

Number of conductors: 1

With concentric shielding: Yes

Connection accessories (included): Screw connector with shear-off head

70 ... 240 mm²

Halogen free: Yes

Packaging

Carton (Default package)

Nominal cross section conductor:

 Package size:
 1 pce

 Depth:
 1043 mm

 Width:
 209 mm

 Height:
 86 mm

 Weight:
 2.595 kg

 Volume:
 18.746882 l

Pallet package

 Package size:
 33 pcs

 Depth:
 1200 mm

 Width:
 800 mm

 Height:
 1000 mm

 Weight:
 105.635 kg

 Volume:
 960 l

