ENSTO

PRODUCT SPECIFICATION



Cold shrink joint

CJ11.42045C

Code CJ11.42045C
GTIN 6438100324803
Name Cold shrink joint

20.8/36 (42) kV 185-400mm² 1-core with

connectors

Description Cold shrink joint for 1-core cables with

Al/Cu conductor, polymeric insulation and

Cu-wire screen. The kit contains components for one cable core.

Mechanical connectors are included in the kit. The joint kits include cold shrinkable joint bodies with integrated geometric stress control elements, tubular copper braids for screen connection, cold

shrinkable outer jacket tubes and all the additional components needed for

assembly.

Vendor Ensto Finland Oy

Technical specification

Features

Rated voltage U0/U (Um): 20.8/36 (42) kV
Shrink technique: Cold shrink

Accessory type: Straight through joint

Conductor material: Al/Cu

Conductor size round: $185 ... 400 \text{ mm}^2$ Screen/shield connection: $≤ 35 \text{ mm}^2$ Installed length (L): 720 mm

Cable

Conductor size Um = 36 kV: 185 ... 400 mm²
Conductor size Um = 42 kV: 185 ... 400 mm²
Diameter on the insulation: 28.6 ... 50 mm
Diameter outer sheath: 33 ... 57 mm



Material insulation: Polymeric

Cu-wire

Number of cores: 1

Temperatures

Material screen/shield:

Installation temperature: $-25 ... 50 \, ^{\circ}\text{C}$ Operating temperature: $-50 ... 90 \, ^{\circ}\text{C}$ Storage temperature: $5 ... 40 \, ^{\circ}\text{C}$

Others

ETIM Class: EC001169

Dimensions

Weight: 3.37 kg

ETIM Technical specification

etim

Rated voltage U0/U (Um):20.8/36 (42) kVModel:Cold-shrinkMaterial insulating material:Plastic

Number of conductors: 1

Nominal cross section conductor: 185 ... 400 mm²

With concentric shielding: Yes

Connection accessories (included): Screw connector with shear-off head

Halogen free: Yes

Packaging

Carton (Default package)

Package size:1 pceDepth:1000 mmWidth:120 mmHeight:110 mmWeight:3.87 kgVolume:13.2 l

Pallet package

Package size:20 pceDepth:1200 mmWidth:800 mmWeight:97.4 kg

